

# Product datasheet

Specifications



## Earth-leakage VigiPacT add-on protection module, ComPacT NSX 250, 200VAC to 440VAC, 30mA to 30A, 4 poles

LV429493

EAN Code: 3606481298591

### Main

Range of product	ComPacT NSX100...250 ComPacT NSX100...250
Device short name	VigiPacT
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPacT ComPacT NSX250 circuit breaker ComPacT ComPacT NSX250 circuit breaker
Poles description	4P
[In] rated current	250 A
Earth-leakage protection class	Class A Class AC
Residual earth-leakage sensitivity adjustment type	Adjustable
Earth-leakage sensitivity	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC
Residual earth-leakage time delay adjustment type	Adjustable
[ $\Delta t$ ] residual earth-leakage time delay adjustment	0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s 4 s

### Complementary

Network type	AC
Network frequency	50/60 Hz
[U <sub>e</sub> ] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Overvoltage category	IV

### Environment

Electrical shock protection class	Class II
-----------------------------------	----------

---

Standards	IEC 60947-2
-----------	-------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	13.500 cm
------------------	-----------

---

Package 1 Width	14.200 cm
-----------------	-----------

---

Package 1 Length	17.200 cm
------------------	-----------

---

Package 1 Weight	1.292 kg
------------------	----------

---

Unit Type of Package 2	S04
------------------------	-----

---

Number of Units in Package 2	12
------------------------------	----

---

Package 2 Height	30.000 cm
------------------	-----------

---

Package 2 Width	40.000 cm
-----------------	-----------

---

Package 2 Length	60.000 cm
------------------	-----------

---

Package 2 Weight	16.204 kg
------------------	-----------

---

Unit Type of Package 3	P12
------------------------	-----

---

Number of Units in Package 3	48
------------------------------	----

---

Package 3 Height	42.000 cm
------------------	-----------

---

Package 3 Width	80.000 cm
-----------------	-----------

---

Package 3 Length	120.000 cm
------------------	------------

---

Package 3 Weight	76.016 kg
------------------	-----------

## Logistical informations

---

Country of origin	IT
-------------------	----

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 30

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number Ef27149b-fb4f-412f-9539-28ab12115a54

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

## Use Longer

### Lifetime extension

Repair No

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins