



S8VK-S06024

Book type power supply, 60 W, 24VDC, 2.5A, DIN rail mounting, Push-in terminal, Coated

Specifications

Type	DIN-rail
Mounting method	DIN rail
Phase	Single
Output voltage	24 V
Power output	60 W
Rated output current	2.5 A
Efficiency	89 %
Power boost ratio	120 %
Temperature range	-40-70 °C
Features	Coated
Terminal type	Push-in
Communication port(s)	None
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	32 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	90 mm

Related products



S8V-NF
Noise Filter S8V-NF



Electronic Circuit Breaker
S8V-CP - Electronic Circuit Breaker

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Perfect Power Supply Solutions
Brochure

EN PDF 1.29 MB



S8VK-S Switch Mode Power Supply
Datasheet

EN PDF 5.72 MB



S8VK-S/S8FS-G
Brochure

EN PDF 2.4 MB



Solution case study No.8 Environment resistance
Brochure

EN PDF 623 KB



T235 Emea S8vk Series Switch Mode Power Supplies
Brochure

EN PDF 1.75 MB



Value Design for Panel Flyer

EN PDF 3.86 MB

