



E3ZM-T86

Photoelectric sensor, rectangular housing, stainless steel, infrared LED, through-beam, 15 m, PNP, Light-ON/Dark-ON, switch output with wire, M8 4-pin connector

Specifications

Shape	Cuboid
Sensing method	Through-beam
Sensing distance	15000 mm
Setting method	Manual adjustment
Connection method	Connector M8 - 4 pin
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	Stainless steel
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	32.2 mm
Product Depth (unpacked)	21 mm
Type of light	Infrared light
Power supply voltage	10-30 V
Degree of protection (IP)	IP67/IP69K

Accessories



E39-L150

Sensor mounting Bracket for E3Z, 100mm high post



E39-L151

Sensor mounting Bracket, for E3Z, 200mm high post



E39-L203

Rear mounting bracket for E3AS-F/L models



E39-L211

L-shaped mounting bracket for E3AS-F/L models



E39-L212

Horizontal protective cover bracket for E3AS-F/L cable and pigtail models



E39-L214

Protective metal cover for E3AS, horizontal surface mounting



E39-L44

Mounting bracket for E3Z sensor, rear mounting


Related products



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

CAD Library



E3Z **Brochure**

EN PDF 1.34 MB



E3ZM Photoelectric Sensor, Compact, Stainless steel **Datasheet**

EN PDF 458 KB



E3ZM-___ **Instruction Sheet**

EN PDF 1.75 MB



EAC Mark removal **Discontinuation Notice**

EN PDF 221 KB