



E3S-CL1-M1J 0.3M

Photoelectric sensor distance setting BGS, 5-200mm, NPN/PNP, M12 pigtail

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	200 mm
Sensing distance (min.)	5 mm
Setting method	Manual adjustment
Connection method	M12 pigtail connector
Cable length	0.3 m
Output type	PNP/NPN
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	Zinc
Thread size	Other
Product Width (unpacked)	15.4 mm
Product Height (unpacked)	43.7 mm
Product Depth (unpacked)	40 mm
Type of light	Polarity free red light
Spot size	18 mm
Power supply voltage	10-30 V
Degree of protection (IP)	IP67

Related products



M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

[CAD Library](#)



E3S-CL Series Datasheet

EN PDF 1.2 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 8 January, 2026. [Click here for terms of use.](#)

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU