



S8VK-S48024

Book type power supply, 480 W, 24 VDC, 20 A, DIN rail mounting, Push-in terminal, Coated, undervoltage alarm

Specifications

Type	DIN-rail
Mounting method	DIN rail
Phase	Single
Output voltage	24 V
Power output	480 W
Rated output current	20 A
Efficiency	93 %
Power boost ratio	150 %
Temperature range	-40-70 °C
Features	Coated
Terminal type	Push-in
Communication port(s)	None
Alarm function	Relay
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	60 mm
Product Height (unpacked)	124 mm
Product Depth (unpacked)	122 mm

Related products



S8V-NF
Noise Filter S8V-NF



Electronic Circuit Breaker
S8V-CP - Electronic Circuit Breaker

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Perfect Power Supply Solutions Brochure

EN PDF 1.29 MB



S8VK-S Switch Mode Power Supply Datasheet

EN PDF 5.72 MB



S8VK-S/S8FS-G Brochure

EN PDF 2.4 MB



Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB



T235 Emea S8vk Series Switch Mode Power Supplies Brochure

EN PDF 1.75 MB



Value Design for Panel Flyer

EN PDF 3.86 MB

