

Product datasheet

Specifications



Polyester glassrein. plinth for encl. PLAZ(T)74 front opening IP44-IK10 RAL7035

Local distributor code:
402658364

NSYZZ274G

EAN Code: 3606480726286

Main

Range	PanelSeT
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth
Application	Multi-purpose
Nominal dimensions of the housing	- D: 420 mm
Device composition	fixing elements 2 front panel 2 side part
Range compatibility	PanelSeT PLA PanelSeT PHD

Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 mm
Width	785 mm
Depth	410 mm

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	43.000 cm
Package 1 Length	81.000 cm
Package 1 Weight	7.762 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	30
Package 2 Height	100.000 cm
Package 2 Width	100.000 cm

Package 2 Length	120.000 cm
------------------	------------

Package 2 Weight	245.000 kg
------------------	------------

Logistical informations

Country of origin	ES
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number

1341ad4e-77b9-40e3-bab0-32043fbc5959

REACH Regulation

[REACH Declaration](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No