




 PRODUCT-DETAILS

3GAA092540-BSK

IE3 Premium Efficiency Aluminum Motors, 1.5 kW, 400 V (3GAA092540-BSK)



General Information

| | |
|----------------------|--|
| Product ID | 3GAA092540-BSK |
| ABB Type Designation | M3AA 90LD 4 |
| Catalog Description | IE3 Premium Efficiency Aluminum Motors, 1.5 kW, 400 V (3GAA092540-BSK) |

Ordering

| | |
|--------------------------------|--|
| ABB Type Designation | M3AA 90LD 4 |
| Invoice Description | M3AA 90LD 4 |
| Product Name | 3-Phase squirrel cage motor |
| Product Type | 3AA3_M3AA_IE3_AA |
| Country or Territory of Origin | China |
| Customs Tariff Number | 85015220 |
| Stocked At (Warehouses) | Menden, Germany Sant Quirze del Vallés - BCN, Spain Shanghai, China Vittuone, Italy |
| Medium Description | 1.5kW, 4 Poles, Frame Size 90, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GAA092540-BSK) |

Short Description

1.5kW, 4P, Frame Size 90, 3PH, 400V, 50Hz, IP55, IMB5/IM3001

Electrical

Electrical Data

| Conn | Temp Class | Network Freq | Network Voltage | Power | Speed | Current | Power Factor | Efficiency | Torque | IS/IN |
|------|------------|--------------|-----------------|---------|------------|---------|--------------|------------|-----------|-------|
| Y | -- | 50 Hz | 400 V | 1.50 kW | 1439 r/min | 3.20 A | 0.780 | 85.30 % | 9.90 N·m | 8.20 |
| D | -- | 50 Hz | 230 V | 1.50 kW | 1439 r/min | 5.60 A | 0.780 | 85.30 % | 9.90 N·m | 8.20 |
| Y | -- | 50 Hz | 380 V | 1.50 kW | 1432 r/min | 3.30 A | 0.810 | 85.30 % | 10.00 N·m | 7.30 |
| D | -- | 50 Hz | 220 V | 1.50 kW | 1432 r/min | 5.70 A | 0.810 | 85.30 % | 10.00 N·m | 7.30 |
| Y | -- | 50 Hz | 415 V | 1.50 kW | 1445 r/min | 3.20 A | 0.750 | 85.30 % | 9.90 N·m | 8.50 |
| Y | -- | 60 Hz | 460 V | 1.50 kW | 1748 r/min | 2.90 A | 0.750 | 86.50 % | 8.10 N·m | 9.50 |

| | |
|----------------------------------|---|
| Connection Configuration | Y |
| Temperature Class Default | -- |
| Input Voltage (U _{in}) | 400 V |
| Frequency (f) | 50 Hz |
| Output Power | 1.5 kW |
| Altitude | 1000 m |
| Ambient Temperature | 40 °C |
| IC Class | IC411 |
| IE Class Data (50 Hz) | IE Class IE3 Full Load (100%) 85.3 % Partial Load (75%) 84.7 % Partial Load (50%) 82.8 % |
| IE Class Data (60 Hz) | IE Class IE3 Full Load (100%) 86.5 % Partial Load (75%) 85.1 % Partial Load (50%) 82.0 % |
| IP Class | IP55 |
| Insulation Class | ICLF |
| Direction of Rotation | Both sides |
| Number of Poles (High) | 4 |
| Two Speed Motor | No |
| Type of Duty | S1 |
| Voltage Code | S |

Mechanical

| | |
|-------------------------|-------------|
| Frame Material | Aluminum |
| Frame Size | 90 |
| Bearing | 6205-2Z/C3 |
| Bearing NDE | 6204-2Z/C3 |
| IM Class | IMB5 IM3001 |
| Terminator Box Location | D-End top |

Dimensions

| | |
|----------------------------|----------|
| Product Net Depth / Length | 331.5 mm |
| Product Net Height | 217 mm |
| Product Net Width | 170 mm |
| Product Net Weight | 19 kg |
| Gross Weight | 22 kg |

Environmental

| | |
|---------------|--|
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| SCIP | 27ac6190-e1ce-4080-8654-6552aaabbe58 Finland |

External Classifications and Standards

| | |
|--------|----------|
| UNSPSC | 26101100 |
|--------|----------|

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

