



175G5238 [🔗](#)

MCD202055T6CV3

MCD202055T6CV3
 VLT® Compact Starter MCD 202
 55 kW 100A:4-6: 594
 Three phase, 200-575 VAC
 Control voltage: 110/240 VAC or 440 VAC
 (B) B-Frame

Model code: MCD202055T6CV3

VLT® Compact Starter MCD 200 from Danfoss includes two families of soft starters in the power range 7.5-110 kW. The series offers easy DIN rail mounting for sizes up to 30 kW, 2-wire or 3-wire start/stop control and excellent starting duty (4 x I_e for 6 seconds). Heavy starting rating at 4x I_e for 20 seconds. Compatible with grounded delta power systems.

PRODUCT DETAILS

Gross weight		4.9 Kilogram
Net weight		4.3 Kilogram
Volume		16.12 Liter
EAN		5702427098770
Product View (Switch)	GLBL	Global (Standard)
Product Group	MCD	VLT® Soft Starter MCD
MCD Series	202	202
Power Rating	055	55 kW 100A:4-6: 594
Phase	T	Three phase
Mains Voltage	6	200-575 VAC
Control Supply Voltage	CV3	110/240 VAC or 440 VAC
Frame Size	B	(B) B-Frame
Typecode Part 1		MCD202055T6CV3
Product Catalog	NO_VIEW	NO VIEW
Modelcode01		MCD202055T6CV3
ECCN EU	Y901	Y901
ECCN US	EAR99	EAR99
Calculated Gross Weight [kg]		4.9
Calculated Net Weight [kg]		4.3
Plant from Orderline	E601	E601
Vendor	ERR01	Cannot Determine Vendor
Producing plant	ERR01	Cannot Determine Vendor
Delivering plant	ERR01	ERR01

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**175G9000** [🔗](#)**Modbus RTU Module, MCD200, MCD500**

Modbus RTU module (RS485) for MCD 200 and MCD 500

**175G9001** [🔗](#)**Profibus Module, MCD200, MCD500**

Profibus option for MCD 200 and MCD 500

**175G9002** [🔗](#)**Devicenet module, MCD200, MCD500****175G9004** [🔗](#)**Remote Operator kit MCD200**

Remote control unit for MCD 200 soft starter.

**175G9009** [🔗](#)**USB Module**

USB module for MCD 200 and MCD 500

**175G9905** [🔗](#)**Profinet module, MCD200, MCD500**

ProfiNet module

**175G9906** [🔗](#)**Ethernet IP module, MCD200, MCD500**

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.