

**088L0993**

**Heating Cables, ECpipeheat 10 V2 readym., 10W/m@10°C, 10 m, Supply voltage [V] AC: 230**

Cable type: Twin conductor, Product version: Ready-made, Heating principle: Self-limiting, Application: Pipe / tank frost protection



**PRODUCT DETAILS**

<b>Gross weight</b>	1.1 Kilogram
<b>Net weight</b>	0.986 Kilogram
<b>Volume</b>	9.147 Liter
<b>EAN</b>	5703466217856
<b>Type</b>	ECpipeheat 10 V2 readym.
<b>Product group</b>	Heating Cables
<b>Application</b>	Pipe / tank frost protection
<b>Approval</b>	UkrTEST CE
<b>Bending diameter [mm] [Min]</b>	50 mm
<b>Cable height [mm]</b>	5.3 mm
<b>Cable length [m]</b>	10 m
<b>Cable on drum</b>	No
<b>Cable output [W/m@°C]</b>	10W/m@10°C
<b>Cable output [W@°C]</b>	100W@10°C
<b>Cable screen</b>	Alufoil 100%
<b>Cable type</b>	Twin conductor
<b>Cable width [mm]</b>	7.7 mm
<b>CE mark</b>	Yes
<b>Certification company</b>	CE EAC UkrTEST
<b>China RoHS compliance</b>	Out of scope
<b>Cold lead</b>	Yes
<b>Cold lead conductor quantity</b>	3
<b>Cold lead length [m]</b>	2 m
<b>Cold lead quantity</b>	1
<b>Conductor insulation</b>	Cross linked polyolefin
<b>Conductor type</b>	Tinned copper
<b>Contains batteries</b>	No
<b>Cut to length</b>	No
<b>Description</b>	ECpipeheat 10 w/plug V2 10m 100W@10°C 230V
<b>EEE category</b>	5 small equipment (any external dimension < 50 cm)
<b>Element IP Class</b>	IPX7
<b>EU RoHS compliance</b>	Yes
<b>EU RoHS exemption clause</b>	No
<b>Filler material</b>	TPE

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## PRODUCT DETAILS

Heating principle	Self-limiting
In scope of WEEE	Yes
Installation temperature [°C] [Min]	-5 °C
Non operating temperature [°C] [Max]	65 °C
Operating temperature [°C] [max]	65 °C
Outer sheath	TPE
Outer sheath colour	Light blue
Package depth [mm]	300 mm
Package height [mm]	60 mm
Package width [mm]	420 mm
Product version	Ready-made
REACH Candidate List substances	No
Supply voltage [V] AC	230 V
UL mark	No
UNSPSC CODE	40101830
Warranty [Year]	5
Warranty type	5-year product warranty

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

## Accessories

**088L3002** [↗](#)**Accessories, Easy Installation Danfoss**

Down Spout Edge Protection Plate (1 / bag), Used for product: ECiceguard 18 Ready-made

**140F0955** [↗](#)**Accessories, Connection kits self-limiting cables**

Con. kit cable/coldlead+end t.(pipeheat), Used for product: DEVIpipeline™ 10 V2 readym.; DEVIpipeline™ 10 V3; DEVIpipeline™ 10 V3 readym.; DEVIpipeline™ 10 V2

**088L0409** [↗](#)**Accessories, Easy Installation Danfoss**

Tape aluminium 38mm x 50m, Used for product: ECpipeheat 10 V3 Ready-made; ECpipeheat 10 V2 Ready-made; EChotwatt; ECflex 10T; ECbasic 20S; ECiceguard 18 Ready-made; ECflex 18T; ECflex 20T; ECpipeheat 10 V2 Drum Goods; ECpipeheat 10 V3 Drum Goods

**140F0954** [↗](#)**Accessories, Connection kits self-limiting cables**

Con. kit cable/jun. box+end t.(pipeheat), Used for product: DEVIpipeline™ 10 V2 readym.; DEVIpipeline™ 10 V3; DEVIpipeline™ 10 V3 readym.; DEVIpipeline™ 10 V2

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

Accessories

---



**19400167** [🔗](#)

**Accessories, Connection kits resistive cables**

Junction box 0,75-2,5 mm<sup>2</sup> 7xM20, Used for product: DEVpipeheat™ 10 V2 readym.; DEVpipeheat™ 10 V3; DEVpipeheat™ 10 V3 readym.; DEVpipeheat™ 10 V2

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.