

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Battery module (device with battery), VRLA-AGM, 48 V DC, 7 Ah



Product description

The maintenance-free lead AGM battery module is an intelligent energy storage device that supports IQ Technology. The process-controlled battery module communicates with the connected QUINT-UPS-IQ device, and is continuously monitored. For mechanical protection, the batteries are located in a robust housing.

Commercial data

Item number	1133819
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CMUEV4
Product key	CMUEV4
GTIN	4063151064877
Weight per piece (including packing)	14,200 g
Weight per piece (excluding packing)	13,600 g
Customs tariff number	85322900
Country of origin	DE

Technical data

Notes

General

Note on the battery	<p>For proper operation of the QUINT-HP-UPS/120AC/2.5KVA/PT (1136813) and QUINT-HP-UPS/230AC/2.5KVA/PT (1136815) uninterruptible power supplies, at least 2 QUINT-HP-BAT/PB/48DC/7.0AH/PT (1133819) battery modules are required.</p> <p>For longer buffer times, multiples of 2 battery modules must always be connected to the UPS (2, 4, 6, 8, or 10). A maximum of 10 batteries can be connected to a single UPS of this type. QUINT-HP-UPS/120AC/1.5KVA/PT (1136804) and QUINT-HP-UPS/230AC/1.5KVA/PT (1136811) can be supplied with individual battery modules (1-5 modules).</p>
---------------------	---

Energy storage

Input

Input voltage	48 V DC (SELV)
Nominal capacity	7 Ah
Charging current	2.1 A
End-of-charge voltage	56 V DC (20 °C)

Output

Output current	40 A
Output fuse	max. 40 A

General

Connection in parallel	yes
	max. 5
Battery type	BB Battery BP7-12FR
Battery technology	VRLA-AGM
IQ-Technology	yes
Latest startup date (battery only)	12 Months (0 °C ... 20 °C)
Latest startup (battery only) - range	9 Months ... 12 Months (20 °C ... 30 °C)
	6 Months ... 9 Months (30 °C ... 40 °C)
Accumulator module service life (according to Eurobat)	6 (20 °C)
Size designation	Block
Suitable for fast charging	yes
Temperature sensor	yes

Connection data

Battery

Position	4.x
----------	-----

Connection technology

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Position marking	4.1 (+), 4.2 (+)
------------------	------------------

Conductor connection

Connection method	Push-in connection
rigid	6 mm ² ... 16 mm ²
flexible	6 mm ² ... 16 mm ²
flexible with ferrule without plastic sleeve	6 mm ² ... 16 mm ²
flexible with ferrule with plastic sleeve	6 mm ² ... 16 mm ²
AWG	8 ... 6
Stripping length	18 mm

Battery

Position	4.x
----------	-----

Connection technology

Position marking	4.3 (-), 4.4 (-)
------------------	------------------

Conductor connection

Connection method	Push-in connection
rigid	6 mm ² ... 16 mm ²
flexible	6 mm ² ... 16 mm ²
flexible with ferrule without plastic sleeve	6 mm ² ... 16 mm ²
flexible with ferrule with plastic sleeve	6 mm ² ... 16 mm ²
AWG	8 ... 6
Stripping length	18 mm

Product properties

Product family	Battery module (device with battery)
----------------	--------------------------------------

Insulation characteristics

Protection class	III
Degree of pollution	2

Dimensions

Item dimensions

Width	156.5 mm
Height	354 mm
Depth	143 mm

Drill hole

Diameter	5.5 mm
----------	--------

Installation dimensions

Installation distance right/left	0 mm / 0 mm
Installation distance top/bottom	20 mm / 20 mm

Environmental and real-life conditions

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C ... 40 °C
Ambient temperature (charge)	0 °C ... 40 °C
Ambient temperature (discharge)	-20 °C ... 50 °C
Max. permissible relative humidity (operation)	≤ 95 %

Ex data


Suited for EX-applications	no
----------------------------	----

1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Drawings

Graphic




The data is based on an ambient temperature of +25 °C at the start of use.



Buffer times for QUINT HP UPS 1.5 kVA

Graphic



The data is based on an ambient temperature of +25 °C at the start of use.



Buffer times for QUINT HP UPS 2.5 kVA

1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1133819>



IECEE CB Scheme

Approval ID: DK-134725-A1-UL



cULus Listed

Approval ID: E123528-20220920



cULus Listed

Approval ID: E199827-20221028

1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Classifications

ECLASS

ECLASS-13.0	27050403
ECLASS-15.0	27050403

ETIM

ETIM 10.0	EC003893
-----------	----------

UNSPSC

UNSPSC 21.0	26111700
-------------	----------

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/gb/products/1133819>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
-------------------------------------	----------------------

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk