

# Product datasheet

Specifications

Schneider Electric NSYPLA1276TG

Picture

Floor standing encl. polyester  
vers.PLA compl.sealed  
1250x750x620 IP65 glazed

NSYPLA1276TG

EAN Code: 3606485434476

## Main

Range	PanelSeT
Product name	PanelSeT PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	1250 mm
Nominal width	750 mm
Nominal depth	620 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door

## Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	1 door(s)
Door opening side	Reversible (120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	UL 508 A IEC 62208
NEMA degree of protection	NEMA 3 NEMA 3S NEMA 13 NEMA 5 NEMA 1 NEMA 12 NEMA 2 NEMA 3X NEMA 3R

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

<b>Product certifications</b>	DNV Marine UL/cUL listed Veritas
-------------------------------	--

---

<b>Electrical insulation class</b>	Class II
------------------------------------	----------

---

## Environment

---

<b>IP degree of protection</b>	IP65 conforming to IEC 60529 (completely sealed)
--------------------------------	--

---

<b>IK degree of protection</b>	IK08 conforming to IEC 62262 (glazed door)
--------------------------------	--

---

<b>Fire resistance</b>	960 °C conforming to IEC 62208
------------------------	--------------------------------

---

<b>Ambient air temperature for storage</b>	-35...90 °C
--	-------------

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	65.000 cm
-------------------------	-----------

---

<b>Package 1 Width</b>	78.000 cm
------------------------	-----------

---

<b>Package 1 Length</b>	126.000 cm
-------------------------	------------

---

<b>Package 1 Weight</b>	47.000 kg
-------------------------	-----------

---

## Logistical informations

---

<b>Country of origin</b>	ES
--------------------------	----

---

## Contractual warranty

---

<b>Warranty (in months)</b>	18
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	366 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	171 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	93 kg CO2 eq.
Carbon footprint of the installation phase [A5]	16 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	86 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	1341ad4e-77b9-40e3-bab0-32043fbc5959
REACH Regulation	<a href="#">REACH Declaration</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions

---

Image of product in real life situation

