


# Product datasheet

Specifications



## CONNECTOR 20A FUSE BS88A1

Local distributor code:

2223474

KSB20CG5

EAN Code: 3606480005930

### Main

Range of product	Canalis
Range compatibility	Canalis KS busbar trunking
Product or component type	Tap-off unit
busbar trunking compatibility	Canalis KS busbar trunkingplug-in
[Ie] rated operational current	20 A at 35 °C
protection type	fuse isolator: BS88 fuse, size A1 conforming to BS
Provided equipment	fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

### Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Cable clamp terminal - ISO32 6 mm <sup>2</sup> flexible Cable clamp terminal - ISO32 10 mm <sup>2</sup> rigid
door/cover opening side	Front
Tap-off unit disconnection mode	By drawing out
Standards	IEC 61439-1 IEC 61439-6
Body material	Plastic
Width	135 mm
Depth	103 mm
Height	165 mm
Net weight	0.6 kg

### Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529

---

<b>IK degree of protection</b>	IK08 conforming to IEC 62262
--------------------------------	------------------------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	16.000 cm
-------------------------	-----------

---

<b>Package 1 Width</b>	17.500 cm
------------------------	-----------

---

<b>Package 1 Length</b>	13.600 cm
-------------------------	-----------

---

<b>Package 1 Weight</b>	666.000 g
-------------------------	-----------

---

<b>Unit Type of Package 2</b>	P12
-------------------------------	-----

---

<b>Number of Units in Package 2</b>	119
-------------------------------------	-----

---

<b>Package 2 Height</b>	80.000 cm
-------------------------	-----------

---

<b>Package 2 Width</b>	80.000 cm
------------------------	-----------

---

<b>Package 2 Length</b>	120.000 cm
-------------------------	------------

---

<b>Package 2 Weight</b>	94.254 kg
-------------------------	-----------

## Contractual warranty

---

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant

SCIP Number

Cb1a2eb4-9b7e-4708-8b1b-be81799688d2

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free product

PVC free

Yes

Silicone-free

Yes

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture


End of life manual availability

No need of specific recycling operations

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins