


Product datasheet

Specifications



TAP OFF UNIT 400A COMPACT NS

Local distributor code:
23350847

KSB400DC4

EAN Code: 3606480005794

Main

Range of product	Canalis
Range compatibility	Canalis KS busbar trunking Canalis KT busbar trunking
Offer type	Classic
Product or component type	Tap-off unit
[Ie] rated operational current	400 A at 35 °C
Protection type	Circuit breaker: Compact NSX400
Provided equipment	circuit-breaker to be ordered separately
Mounting mode	Plate with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	400 V depending on protective device 500 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	400 V depending on protective device 500 V depending on protective device
Network frequency	50/60 Hz
Control type	Extended rotary handle
Electrical connection	Crimp lug - ISO50 240 mm ² flexible Crimp lug - ISO50 240 mm ² rigid
door/cover opening side	Right
Tap-off unit disconnection mode	By rotary operating handle
Number of openings	2 openings for FL21 gland plate
Standards	IEC 61439-6 IEC 61439-1
Body material	Metal
Width	700 mm
Depth	350 mm
depth (door open)	976.5 mm
Height	400 mm
Net weight	19 kg

Environment

Earthing system	TT TN-S IT
-----------------	------------------

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

IK degree of protection	IK08 conforming to IEC 62262
-------------------------	------------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	38.5 cm
------------------	---------

Package 1 Width	45.6 cm
-----------------	---------

Package 1 Length	76.0 cm
------------------	---------

Package 1 Weight	19.261 kg
------------------	-----------

Unit Type of Package 2	P12
------------------------	-----

Number of Units in Package 2	4
------------------------------	---

Package 2 Height	90.0 cm
------------------	---------

Package 2 Width	80.0 cm
-----------------	---------

Package 2 Length	120.0 cm
------------------	----------

Package 2 Weight	89.044 kg
------------------	-----------

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

Fbe82b7c-542c-4391-913a-58c8f489ca40

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free product

PVC free

Yes

Silicone-free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins