

**032U7120****Solenoid valve, EV220B, Function: NC, G, 3/4, 8 m³/h, EPDM**

Media recommendations: Water & Brine, Approval: DNVGL-CG-0339; GL; PZH,
Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

PRODUCT DETAILS

Gross weight	0.917 Kilogram
Net weight	0.87 Kilogram
Volume	0.88 Liter
EAN	5702423009510
Type	EV220B
Product group	Solenoid valves
Product Name Description	Solenoid valve
Actuator	B
Actuator size	13.5 mm
Actuator size [in]	0.53 in
Actuator system [mm]	13.5 mm
Ambient temperature max. [°C]	80 °C
Ambient temperature max. [°F]	176 °F
Application	Open
Body material	Brass
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.3
Connection Internal/External	Internal
Connection material	Brass
Connection size [in]	3/4
Connection standard	ISO 228-1
Connection type	G
Contains batteries	No
Cv value [gal/min]	9.25 gal/min
Differential pressure [bar] [max]	16 bar
Differential pressure [bar] [min]	0.3 bar
Differential pressure [psi] [max]	232 psi
Differential pressure [psi] [min]	4.35 psi
EEE category	5 small equipment (any external dimension < 50 cm)
Est. time to open, water [ms]	40 ms
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flow direction	Single-flow
Flow direction indicator	Embossed 1-way arrow
Fluid Group	1
Function	NC
Identical product	032U8120

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Solenoid valve, EV220B, Function: NC, G, 3/4, 8 m³/h, EPDM
PRODUCT DETAILS

In scope of WEEE	Yes
Kv value [m³/h]	8 m ³ /h
Max media viscosity [cSt]	50 cSt
Max. test pressure [bar]	24 bar
Max. test pressure [psig]	348 psig
Max. Working Pressure [bar]	16 bar
Max. Working Pressure [psig]	232 psig
Media recommendations	Water & Brine
Media tolerance comments	Neutral media Steam Max 4 bar Temperature: Coil dependent
Medium temperature range [°C] [max]	120 °C
Medium temperature range [°C] [min]	-30 °C
Medium temperature range [°F] [max]	248 °F
Medium temperature range [°F] [min]	-22 °F
Number of ways	2/2
Open/close equalizing orifice	Optional Equalization orifice
Operation	Servo-operated (diaphragm)
Orifice size [mm]	20 mm
Orifice size fraction [in]	3/4 in
Packing format	Multi pack
Parts Program name	EV220B 15 - 50
Product accessories	Solenoid valve accessories
Quantity per packing format	24 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
SCIP dossier no.	b8af40bc-3f7f-4177-bd55- c3503ccccfc04
SCIP dossier product name	EV220B 15-50 brass NC - solenoid valve
Seal Material	EPDM
Serviceable	Solenoid valve spare parts
Specification key	EV220B 20B G 34E NC000
Type designation	EV220B 20

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

018F7351 [🔗](#)

Solenoid coil, BB230AS, DIN Spade, Supply voltage [V] AC: 230, Multi pack

Electrical connection: DIN Spade, Supply voltage [V] AC: 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**018F7358** [🔗](#)**Solenoid coil, BB024AS, DIN Spade, Supply voltage [V] AC: 24, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

**018F7397** [🔗](#)**Solenoid coil, BB024DS, DIN Spade, Supply voltage [V] DC: 24, Multi pack**

Solenoid coil, Product Type: BB024DS, Supply voltage [V] DC: 24, Enclosure rating IP: IP00, Coil connection: DIN Spade, Actuator size: 13.5 mm

**018F7396** [🔗](#)**Solenoid coil, BB012DS, DIN Spade, Supply voltage [V] DC: 12, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] DC: 12, Enclosure rating IP: IP00

**032U0150** [🔗](#)**Spare part, EV220B 15-32, Sub-part**

Product Type: Spare part, Used for product: EV220B 15-32, Type designation: Sub-part, Manual opening

**032U7390** [🔗](#)**Spare part, EV220B 15-50; EV220B 65-100; EV220B 15-100, Actuator set manual override**

Product Type: Spare part, Used for product: EV220B 15-50; EV220B 65-100; EV220B 15-100, Type designation: Actuator set manual override, Service kit, Function: NC

**018F6701** [🔗](#)**Solenoid coil, BE230AS, Terminal box, Supply voltage [V] AC: 220 - 230, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 220 - 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67

**018F6707** [🔗](#)**Solenoid coil, BE024AS, Terminal box, Supply voltage [V] AC: 24, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67

**018F6783** [🔗](#)**Solenoid coil, BE240CS, Terminal box, Supply voltage [V] AC: 208 - 240, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 208 - 240, Frequency [Hz]: 50/60 Hz, Enclosure rating IP: IP67

**042N7501** [🔗](#)**Solenoid coil, BA230A, DIN Spade, Supply voltage [V] AC: 220 - 230, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] AC: 220 - 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



042N7508 [↗](#)

Solenoid coil, BA024A, DIN Spade, Supply voltage [V] AC: 24, Multi pack

Electrical connection: DIN Spade, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00



042N7551 [↗](#)

Solenoid coil, BA024D, DIN Spade, Supply voltage [V] DC: 24, Multi pack

Electrical connection: DIN Spade, Supply voltage [V] DC: 24, Enclosure rating IP: IP00

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.