



## E2E-X5B1T18 5M

Proximity sensor, inductive, nickel-brass, short body, M18, shielded, 5 mm, DC, 3-wire, PNP NO, IO-Link COM3, 5 m cable

# Specifications

Size	M18
Mounting type	Flush
Sensing distance	5 mm
Overall length of sensor	55.3 mm
Thread length	34 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Cable
Cable specifications	PVC (oil-resistant)
Cable length	5 m
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP67G/IP69K

# Accessories



Y92E-J18S30

Mounting Sleeves e-jig for M18 Prox

## CAD Library



### E2E NEXT Datasheet

EN PDF 40 MB



### E2E(Q) - Basic Models Index list

EN PDF 7.27 MB



### E2E(Q) - Premium Models Index list

EN PDF 719 KB



### E2E(Q)- XB\_XC\_basic\_model Instruction Sheet

EN PDF 2.28 MB



### E2E[Q]-XxBxxxx IO-Link IODD file

EN ZIP 1.35 MB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 6.41 MB