


# Product datasheet

Specifications



## SCREW TERMINAL, FEED THROUGH, 3 POINTS, 4MM<sup>2</sup>, GREY

Local distributor code:  
397144640

NSYTRV43

EAN Code: 3606480531972

### Main

Range	Linery
Product name	Linery TR
Product or component type	Terminal block
Device short name	TRV
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	4 mm <sup>2</sup>
Length	57.8 mm
Colour	Grey
Quantity per set	Set of 50

### Complementary

Width	6.2 mm
Height	47.5 mm
Connections - terminals	1 x screw terminal: upstream (M3) 2 x screw terminal: downstream (M3)
number of connections	3
Connection position	Sideways
Number of measurement input	2
Cable cross section	0.14...6 mm <sup>2</sup> , solid cable with cable end 0.2...4 mm <sup>2</sup> , flexible cable with cable end 0.14...6 mm <sup>2</sup> , flexible cable without cable end 0.14...6 mm <sup>2</sup> , solid cable without cable end
Tightening torque	0.6...0.8 N.m
Wire stripping length	9 mm
Tool type	Connection: screwdriver Disconnection: screwdriver
[Ue] rated operational voltage	500 V conforming to EN/IEC 60947-7-1 150 V UL
[In] rated current	32 A conforming to EN/IEC 60947-7-1 30 A UL

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Material</b>	Polyamide 6/6: insulating case Copper alloy: connector and screw Copper alloy: commoning link Chromium-nickel steel: spring
<b>Dielectric loss</b>	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
<b>Dielectric constant</b>	3.7 at 1 MHz
<b>Resistivity</b>	10000 M $\Omega$ .m conforming to IEC 60093 10000 M $\Omega$ .m conforming to VDE 0303-T30
<b>Surface resistance</b>	1000 G $\Omega$ conforming to IEC 60093 1000 G $\Omega$ conforming to VDE 0303-T30
<b>Creep resistance</b>	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
<b>Flame retardance</b>	V0, thickness 0.8 mm conforming to UL 94
<b>Net weight</b>	14 g
<b>Range compatibility</b>	PrismaSeT G PrismaSeT P PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
<b>Product compatibility</b>	Spacial enclosures

## Environment

<b>Product certifications</b>	CSA UL GL DNV
<b>Dielectric strength</b>	1000 V conforming to IEC 60243-1
<b>Ambient air temperature for operation</b>	-40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.300 cm
<b>Package 1 Width</b>	6.100 cm
<b>Package 1 Length</b>	7.950 cm
<b>Package 1 Weight</b>	13.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	50
<b>Package 2 Height</b>	5.300 cm
<b>Package 2 Width</b>	6.100 cm
<b>Package 2 Length</b>	31.800 cm
<b>Package 2 Weight</b>	689.000 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	500
<b>Package 3 Height</b>	30.000 cm

---

Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	7.353 kg

---

## Logistical informations

---

Country of origin	DE
-------------------	----

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	6 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	8e5413ff-f1a1-4909-ad03-977097e33bd2
REACH Regulation	<a href="#">REACH Declaration</a>
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

### Use Longer




### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

Recyclability potential, in %	46
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins