



 PRODUCT-DETAILS

CPC20/50M

20MM SOLID PE CONDUIT 50M - BL



General Information

Extended Product Type	CPC20/50M
Product ID	7TCA298000R0009
EAN	5020963785870
Catalog Description	20MM SOLID PE CONDUIT 50M - BL
Long Description	Flame Retardant, Highly Flexible Conduit, NC Size 20/NW Size 17, Outside Diameter 21.2mm, Inside Diameter 16.1mm, Static Bend Radius 40mm, Very High UV Resistance and Fatigue Life, IP40 Rating, FR Co-Polyester, Reel Length 50 Meters, Black

Additional Information

Product Main Type	HARNESSFLEX FLEXIBLE CABLE PROTECTION
Application	Ideal for Harness Applications Such as Engine, Body Section and Chassis. CPC is Resistant to Hydrocarbons, Greases, Fuels and Oils

Ordering

EAN	5020963785870
UPC	786210273709

Dimensions

Outside Diameter	21.2 mm
------------------	---------

Technical

Number of Batteries	0
Color	Black
Material	Fire Resistant Co-Polyester

Environmental

WEEE Category	Product Not in WEEE Scope
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	5020963785870
Package Level 1 Height	7.87 in 200 mm
Package Level 1 Depth / Length	17.32 in 440 mm
Package Level 1 Width	17.32 in 440 mm

Certificates and Declarations

Declaration of Conformity - CE	9AKK107492A9616
RoHS Declaration	9AKK107992A8994
REACH Declaration	9AKK107992A8994

External Classifications and Standards

ETIM 8	EC001175 - Corrugated plastic hose
ETIM 9	EC001175 - Corrugated plastic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

