



IEC guide frame, frame size 1; rated current $\leq 2000\text{A AC}$; breaking capacity M; 3-pole; connection horizontal, with two-piece shutter, interlockable any circuit breaker or non automatic circuit breaker with COM with position signaling switch switch PSS (1x, 1x, 1x + COM) . Option N03 = Secondary disconnect system with screw type terminals instead of Push-In technology.

Model	
product brand name	SENTRON
size of the circuit-breaker	1
number of poles	3
design of the product	AC
type of electrical connection	suitable for circuit breakers: 630 A to 2000 A
type of electrical connection / for main current circuit	rear horizontal
pack type	standard packaging
Weight	42.483 kg
Net Weight	27.483 kg

Approvals / Certificates		
General Product Approval	EMV	Test Certificates

[Confirmation](#)



[Miscellaneous](#)

Maritime application	other
----------------------	-------



[Confirmation](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA8120-4AA32-1BG1-Z N03>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3WA8120-4AA32-1BG1-Z N03>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA8120-4AA32-1BG1-Z N03
- CAX-Online-Generator
<https://www.siemens.com/cax>
- Characteristic curves
[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



last modified:

1/27/2026

