



**195N1039**

**VLT2815PT4B20STR1DBF00A00C0**

This product is not available in this store. Please contact your local **Customer Service Center**.

There is a newer, improved version of the product that Danfoss recommends you investigate.

Please explore the options using the conversion tool.

**Conversion Tool**

VLT2815PT4B20STR1DBF00A00C0

VLT® 2800 Serie

1.5kW / 2.0 HP, 3X380-480V 50/60Hz,

EN 55011 Class A1, IP20

**Model code:** VLT2815PT4B20STR1DBF00A00C0

Successor product: VLT® Midi Drive FC 280

The VLT® Midi Drive FC 280 is more than just a successor; it is simply the best alternative. As well as full backwards compatibility, it offers a number of additional functions which make this new drive flexible, communicative, easy to use and the best fit for your application.

Power range

1 x 200-240 V.....0.37-2.2 kW

3 x 220-240 V.....0.37-3.7 kW

3 x 380-480 V.....0.37-22 kW

**View Efficiency Data**

**PRODUCT DETAILS**

<b>Gross weight</b>		2.75 Kilogram
<b>Net weight</b>		2.5 Kilogram
<b>Volume</b>		16.53 Liter
<b>EAN</b>		5702427034099
<b>Product View (Switch)</b>	GLBL	Global (Standard)
<b>Product Group</b>	VLT	VLT®
<b>VLT Series</b>	28	2800
<b>Power Rating</b>	15	1.5kW / 2.0 HP
<b>Dedicated Application</b>	P	Process
<b>Phase</b>	T	3 phase
<b>Mains Voltage U(in)</b>	4	380-480V +/- 10% 50/60Hz
<b>Enclosure Type</b>	B	Bookstyle
<b>Enclosure Class</b>	20	IP20
<b>Hardware Configuration</b>	ST	Standard
<b>RFI Filter</b>	R1	EN 55011 Class A1
<b>Display</b>	DB	Built In Display (SLCP)
<b>Fieldbus Option</b>	F00	Without fieldbus option
<b>Application Option</b>	A00	No application option
<b>Coating</b>	C0	Without coating
<b>Frame Size</b>	A	A-Frame
<b>Product Catalog</b>	NO_VIEW	NO VIEW

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | VLT2815PT4B20STR1DBF00A00C0

## PRODUCT DETAILS

Height [mm]	200	200
Width w/ no C options [mm]	75	75
Depth [mm]	168	168
Weight [kg]	2.1	2.1
kVA	2.6	2.6
Calculated Gross Weight [kg]		2.4
Calculated Net Weight [kg]		2.1
ECCN EU	Y901	Y901
ECCN US	3A999.a	3A999.a
Vendor	ERR01	Cannot Determine Vendor
Producing plant	ERR01	Cannot Determine Vendor
Modelcode01		VLT2815PT4B20STR1DBF00A00C0
Delivering plant	ERR01	ERR01
Typecode Part 1		VLT2815PT4B20STR1DBF00A00C0

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

## Accessories

**175N0128** [↗](#)**Local Operation Pad LOP**

Panel for start/stop and setting the reference

**175Z0929** [↗](#)**LCP Cable, 3m**

Cable for control panel (LCP), 3 meters Works with the following LCP:

Alphanumeric control panel LCP3 - 175N0131

VLT® LCP 102 Graphic Display - 130B1107

VLT® LCP 101 Numeric Display - 130B1124

VLT® LCP 102 Graphic display IP66 - 130B1078

Product group: F1

**195N2179** [↗](#)**IP21 conversion kit, top, A**

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.