

Product datasheet

Specifications



APC Easy UPS 1 Ph Line Interactive, 3kVA, Tower, 230V, 6 IEC C13 outlets, AVR, Dry Contact, LCD, Without Network Card support

SMV3000CAI

EAN Code: 0731304346555

Overview

Presentation	Easy UPS provides power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Input Connection Type	IEC 60320 C20
Input voltage limits	165...295 V
Network frequency	45...65 Hz +/- 1 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	2100 W
rated power in VA	3000 VA
Output connection type	6 IEC 60320 C13
Crest factor	3 : 1
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
Transfer time	2-6 ms typical : 12 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 1 Hz unsynchronised

Complementary



Battery type	Lead-acid internal included
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port
Surge energy rate	125 J
Number of cables	1


Colour	Black
Height	240 mm
Width	180 mm
Depth	455 mm
Net weight	25.2 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Mounting mode	Tower
Provided equipment	Documentation CD User manual USB cable
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE UKCA EAC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-10...40 °C
Storage altitude	0...15000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	45 dBA
Operating altitude	0...3000 m

Batteries & Runtime

Run Time	View Runtime Graph 
Efficiency	View Efficiency Graph 
Battery type	Lead-acid battery
Battery voltage	48 V
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0

Battery recharge time	4 h
Battery life	3...5 year(s)
Replacement battery	APCRBCV209 
Battery charger power	99 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	41.400 cm
Package 1 Width	31.900 cm
Package 1 Length	60.400 cm
Package 1 Weight	28.839 kg
Unit Type of Package 2	P12
Number of Units in Package 2	12
Package 2 Height	13.200 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	346.068 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	1 968 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	614 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	7 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 341 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACH Regulation	REACH Declaration

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again

Repack and remanufacture


Recyclability potential, in %	58
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

