



 PRODUCT-DETAILS

A110-30-00-80

A110-30-00 220-230V 50Hz / 230-240V 60Hz
 Contactor

"No longer for sale" replaced by



General Information

Extended Product Type	A110-30-00-80
Product ID	1SFL451001R8000
EAN	7320500129319
Catalog Description	A110-30-00 220-230V 50Hz / 230-240V 60Hz Contactor
Long Description	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 1000 V. Operated with control voltage, versions from 24V AC, 50 and 60 Hz

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SFL427001R1300

Popular Downloads

Data Sheet, Technical	1SBC100192C0206
-----------------------	-----------------

Information

Instructions and Manuals	5309660-60
--------------------------	------------

Dimensions

Product Net Width	90 mm
Product Net Depth / Length	123.5 mm
Product Net Height	148 mm
Product Net Weight	1.8 kg
Dimension Diagram	53540923-1

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Number of Poles	3P
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 160 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 160 A (690 V) 55 °C 145 A (690 V) 70 °C 130 A
Rated Operational Current AC-3 (I_e)	(415 V) 55 °C 110 A (440 V) 55 °C 100 A (500 V) 55 °C 100 A (690 V) 55 °C 82 A (1000 V) 55 °C 30 A (380 / 400 V) 55 °C 110 A (220 / 230 / 240 V) 55 °C 110
Rated Operational Current DC-1 (I_e)	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
Rated Operational Current DC-3 (I_e)	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
Rated Operational Current DC-5 (I_e)	(110 V) 2 Poles in Series, 40 °C 160 A (220 V) 3 Poles in Series, 40 °C 160 A
Rated Operational Power AC-3 (P_e)	(415 V) 59 kW (440 V) 59 kW (500 V) 59 kW (690 V) 75 kW (1000 V) 40 kW (380 / 400 V) 55 kW (220 / 230 / 240 V) 30 kW
Rated Breaking Capacity AC-3	8 x I_e AC-3
Rated Making Capacity AC-3	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 200 A
Rated Short-time Withstand Current Low	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 800 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 175 A

Voltage (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 350 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1320 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 500 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 1160 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 800 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A
Power Loss	at Rated Operating Conditions per Pole 3.6 W
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 15 ms Between Coil Energization and NO Contact Closing 10 ... 25 ms
Connecting Capacity Main Circuit	Bar 30 mm ² Flexible with Cable End 1 x 10 ... 70 mm ² Rigid 2 x 6 ... 65 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Connecting Capacity	Bar 30 mm ² Flexible with Cable End 2 x 6 ... 35 mm ² Rigid 2 x 6 ... 65 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M8 hexagon socket screw with single connector
Tightening Torque	Main Circuit 8 N·m
Terminal Type	Cable Clamp
Product Name	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 140 A
Horsepower Rating UL/CSA	(200 V AC) Three Phase 30 hp (208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 40 hp (440 ... 480 V AC) Three Phase 75 hp (550 ... 600 V AC) Three Phase 100 hp
Full Load Amps Motor Use	(440 ... 480 V AC) Three Phase 96 A (550 ... 600 V AC) Three Phase 99 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 10 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B1 5 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B2 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C2 20 g

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

BV Certificate	07172/D0 BV
CB Certificate	SE-69487
CQC Certificate	CQC2002010304008904 CQC2009010304353526
CSA Certificate	314005
Declaration of Conformity - CCC	2020980304001630 2020980304001078
Declaration of Conformity - CE	2CMT2015-005436
Declaration of Conformity - UKCA	2CMT2020-006118
DNV Certificate	DNV_E-12191
GL Certificate	GL_99358-97HH
LOVAG Certificate	SE-9645071-2
LR Certificate	LR_12-70027-E1
RINA Certificate	ELE060313XG/001
RMRS Certificate	RMRS_12-03683-315

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	162 mm
Package Level 1 Gross Weight	2 kg
Package Level 1 EAN	7320500129319

External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors
E-Number (Finland)	3709350
E-Number (Norway)	4115026

Where Used (as a spare part for "Products")

Identifier	Description	Quantity	Unit Of Measure
3HAC020536-014	No Description Available	1	piece

Product specific part data

Product	Robotics Part Category	Robot Design Year
3HAC020536-014	Process Module	IRC5 M2004

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → A Contactors
 Robotics → Controllers → IRC5 → IRC5 Single

