



 PRODUCT-DETAILS

N2285.4 PL

USB charger Breakout cable with USB A/C Silver - Zenit



General Information

Extended Product Type	N2285.4 PL
Product ID	2CLA228540N1301
EAN	8427238271279
Catalog Description	USB charger Breakout cable with USB A/C Silver - Zenit
Long Description	Color: Silver. Input voltage: 100 - 240 Vac \pm 10%; 50/60 Hz. Input current (max.): 350 mA. Output power (max.): 15 W. Output voltage USB-A: 5 Vdc (max. 2,4 A). Output voltage USB-C: 5 Vdc (max. 3 A). Output voltage USB-A+C: 5 Vdc (total max. 3A). Power consumption in stand-by: \leq 70 mW. Efficiency: > 86%. Size: 2 modules.

Installation

Instructions and Manuals	2CLX210109N1001
Mounting Type	Module frame

Environmental

Degree of Protection	IP20
----------------------	------

Technical

Data Sheet, Technical Information	9AKK107045A9768
Number of Outputs	2
Connection Type	Push-In
USB Port Type	USB A/C

Electrical

Operational Voltage	100 ... 240 V
Output Voltage (U_{out})	5 V
Output Current Maximum (I_{out})	2100 mA
Rated Frequency (f)	50 ... 60 Hz

Design

Design Range	Zenit
Surface Finishing	Decor Matt
Material	Plastic Thermoplastic
Color	Silver

Dimensions

Product Net Width	22 mm
Product Net Height	44 mm
Product Net Depth / Length	44 mm
Product Net Weight	56 g

Ordering

Replaced Product ID (OLD)	2CLA228500N1301
---------------------------	-----------------

Material Compliance

RoHS Information	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Certificates and Declarations

Declaration of Conformity - CE	9AKK108471A3850
EU Data Act Applicability and Compliance	Not Applicable

External Classifications and Standards

ETIM 9	EC002949 - USB power supply
ETIM 10	EC002949 - USB power supply
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Socket Outlets

