



 PRODUCT-DETAILS

M1011-T13

M1011-T13 Socket outlet



General Information

| | |
|-----------------------|---|
| Extended Product Type | M1011-T13 |
| Product ID | 2CSM220685R0721 |
| EAN | 8012542206859 |
| Catalog Description | M1011-T13 Socket outlet |
| Long Description | <p>The Modular sockets M1011 in grey allow the connection of devices, tools or electrical and electronic non modular equipments in civil and industrial electrical switchboards.</p> <p>The M1011 series, with SEV certification, allows to plug four types of swiss standard plugs, single- and three-phase with currents up to 16 A. They can be mounted on DIN rail or Smisline rails without supply connection.</p> |

Technical

| | |
|--------------------------------|---|
| Number of Active Pin Terminals | 2 |
| Tightening Torque | 2.8 N·m |
| Product Type | Swiss Standard |
| Cable Cross-Section | Minimum 1 mm ² Maximum 25 mm ² |
| Connecting Capacity | Rigid Cu-Cable 1 ... 25 mm ² |

Electrical

| | |
|---------------------------------|---------------------------------------|
| Rated Voltage (U _r) | 250 V AC |
| Rated Current (I _n) | 10 A |
| Rated Frequency (f) | 50/60 Hz |
| Power Loss | at Rated Current 0.6 W Total 0.6 W |

Design

| | |
|-------|------|
| Color | Grey |
|-------|------|

Material Compliance

| | |
|---|--|
| RoHS Declaration | 9AKK108469A3593 |
| RoHS Information | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20240711 |
| REACH Declaration | 9AKK108467A9482 |
| REACH Information | False - does not contain substances > 0.1 mass percentage |
| REACH Date | 20250225 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

Environmental

| | |
|---------------------------|---|
| Ambient Air Temperature | Operation -5...+35 °C Storage -40...+70 °C |
| Degree of Protection | IP20 |
| Environmental Information | 9AKK108471A0778 |

Dimensions

| | |
|-------------------------------------|-----------------|
| Width in Number of Modular Spacings | 3 |
| Product Net Width | 53 mm |
| Product Net Height | 85 mm |
| Product Net Depth / Length | 70 mm |
| Product Net Weight | 0.134 kg |
| Built-In Depth (t ₂) | 60 mm |
| Dimension Diagram | 9AKK108469A2299 |

Ordering

| | |
|------------------------------|----------|
| Package Level 1 Units | 2 piece |
| Package Level 1 Gross Weight | 0.178 kg |
| E-Number (Finland) | 2506031 |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK108469A2066 |
| SEV Certificate | 9AKK107991A9777 |

Installation

| | |
|--------------------------|--------------------|
| Instructions and Manuals | No document needed |
|--------------------------|--------------------|

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |
|-----------------------------------|-----------------|

External Classifications and Standards

| | |
|----------------------------|--|
| ETIM 9 | EC001663 - Socket outlet for distribution board |
| ETIM 10 | EC001663 - Socket outlet for distribution board |
| UNSPSC | 39121406 |
| eClass | V11.0 : 27142305 |
| Object Classification Code | X |
| Standards | IEC 60884-1:2002 IEC 60884-1:2002/AMD1:2006 IEC 60884-1:2002/AMD2:2013 SN 441011-1:2019 |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Socket Outlets

