

Pointek CLS300 RF Capacitance point level switch, cable design. Detects level and interface in aggressive liquids, solids, slurries, and foam. Cable extension options to 25 m (82.02 ft), adaptable sensitivity, with active shield to tune out build-up on probe. Process Connection: R 1 1/2" (BSPT), EN 10226/PT (JIS-T), JIS B 0203 Probe Length: (Lengths from flange face) Extended cable, 3000 mm (118.11"), length can be shortened by customer Thermal Isolator: Without thermal isolator Wetted Seals: FKM Probe Material: Bare 316L stainless steel cable, PEEK isolators and 316L stainless steel cable weight Approvals: Flameproof Enclosure with IS Probe: CE, C-TICK, ATEX II 1/2 G EEx d(ia) IIC T6...T1, ATEX II 1/2 D T100 C Enclosure and Lid: Aluminum epoxy coated 2 x M20 x 1.5 cable inlet, IP65 Active Shield Length: Standard length - (125 mm threaded, 105 mm flanged)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

