

**014L0025****SGP 12 I, Sight glass, Flare, 12 mm, Flare, 12 mm**

Inlet connection type: Flare, Inlet size [mm]: 12, Outlet connection type: Flare, Outlet size [mm]: 12, Packing format: Multi pack, Quantity per packing format: 24

PRODUCT DETAILS

Gross weight	0.228 Kilogram
Net weight	0.201 Kilogram
Volume	0.139 Liter
EAN	5702428838535
Type	SGP 12 I
Product group	Sight glasses
Product Name Description	Sight glass
Approval	C UL US LISTED EAC
Approval file name	REF. LIQUID INDICATOR 76H4
Body material	Brass
China RoHS compliance	Yes with exemptions
Connection material	Brass
Contains batteries	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Green: max moist con@25 °C	R22: 150 ppm
Green: max moist con@43 °C	R22: 250 ppm
Identical product	014L0075
Inlet connection type	Flare
Inlet Internal/External	Internal
Inlet size [in]	1/2 in
Inlet size [mm]	12 mm
Max. Working Pressure [bar]	52 bar
Max. Working Pressure [psig]	754 psig
Moisture indicator	I indicator
Outlet connection type	Flare
Outlet Internal/External	External
Outlet size [in]	1/2 in
Outlet size [mm]	12 mm
Packing format	Multi pack
Product accessories	Generic accessories
Quantity per packing format	24 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1) Cobalt dichloride (CAS no. 7646-79-9)
Refrigerants	R22
SCIP dossier no.	967c0700-c0a7-4862- a521-6146e31f5313
SCIP dossier product name	SG & SGP with indicator

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | SGP 12 I, Sight glass, Flare, 12 mm, Flare, 12 mm

PRODUCT DETAILS

Serviceable	No
Temperature range [°C] [max]	80 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	175 °F
Temperature range [°F] [min]	-58 °F
UL approval file name	REF. LIQUID INDICATOR 76H4
UL approved refrigerants	R22
UL mark	Yes
Yellow: min moist con@25 °C	R22: 300 ppm
Yellow: min moist con@43 °C	R22: 500 ppm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.