



060G1051 [🔗](#)

Pressure transmitter, AKS 3000, -1 bar - 9 bar, -14.5 psi - 130.5 psi

Pressure reference: Sealed gauge, Output signal: Current, Electrical connection: Angular connector, Pressure connection type: NPT, Pressure connection size: 1/4-18, Specification key: AKS 3000-D631-A1EC04-0

PRODUCT DETAILS

Gross weight	0.178 Kilogram
Net weight	0.157 Kilogram
Volume	0.411 Liter
EAN	5702423099818
Type	AKS 3000
Product group	Sensors
Product Name Description	Pressure transmitter
+ supply	Pin 1
- common	Pin 2
Accuracy, max. [±FS%]	2 %
Accuracy, typical [±FS%]	1 %
Adj. zero point and span	No
Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	185 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	ATEX GOST POCC CE C UL US UL Recognized
Approval comments	ATEX Ex ec IIA T4 Gc
Approval standard	6967179 E227388 E31024
CE evaluated	Yes
China RoHS compliance	Out of scope
Compensated temp. range [°C] [max]	40 °C
Compensated temp. range [°C] [min]	-30 °C
Compensated temp. range [°F] [max]	104 °F
Compensated temp. range [°F] [min]	-22 °F
Contains batteries	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Pressure transmitter, AKS 3000, -1 bar - 9 bar, -14.5 psi - 130.5 psi
PRODUCT DETAILS

EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector
Electrical connection size	Pg 9
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flush diaphragm	No
High Clipping Level	22.4
In scope of WEEE	Yes
International Article Number	5702423099818
Intrinsically safe	No
Low Clipping level	3.6
Medium temperature range [°C] [max]	85 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	185 °F
Medium temperature range [°F] [min]	-40 °F
Non-linearity BFUL (±FS%)	0.5 %
Output signal	Current
Output signal [mA] [max]	20 mA
Output signal [mA] [min]	4 mA
Overload pressure max. [bar]	33 bar
Packing format	Multi pack
Pressure connection size	1/4-18
Pressure connection standard	ANSI/ASME B1.20.1
Pressure connection type	NPT
Pressure Male/Female	Male
Pressure range [bar] [max]	9 bar
Pressure range [bar] [min]	-1 bar
Pressure range [psi] [max]	130.5 psi
Pressure range [psi] [min]	-14.5 psi
Pressure reference	Sealed gauge
Pulse-snubber	No
Quantity per packing format	14 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Response time max. [ms]	4 ms
SCIP dossier no.	442fa760-b631-4ddb-a979-55b604269353
SCIP dossier product name	Sensor AKS 3000
Specification key	AKS 3000-D631-A1EC04-0
Supply voltage [V] DC [max]	32 V
Supply voltage [V] DC [min]	9 V
UL evaluated	Yes

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

[For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store](#)

Accessories



060G0250 [↗](#)

Accessories, sensors, Process con. adapter

Used for product: AKS/MBS, Parts included: Pulse snubber; Adapter 1/4 NPT, Packing format: Multi pack, Quantity per packing format: 6



060G2850 [↗](#)

Accessories, sensors, Display

Used for product: MBS (4-20mA); MBT5560; MBT 3560; AKS (4-20mA), Parts included: Display, Packing format: Single pack, Quantity per packing format: 1

[For more information, please use this link to visit the product page on Danfoss Product Store](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.