

**084Z4182** [↗](#)**Temperature transmitter, MBT 3560, 70 mm, G,1/2**

Temperature range [°C]: -50 - 200, Electrical connection: Angular connector,  
Electrical connection size: Pg 9, Protection tube material: AISI 316 TI

**PRODUCT DETAILS**

<b>Gross weight</b>	0.199 Kilogram
<b>Net weight</b>	0.151 Kilogram
<b>Volume</b>	0.604 Liter
<b>EAN</b>	5702428927345
<b>Type</b>	MBT 3560
<b>Product group</b>	Sensors
<b>Product Name Description</b>	Temperature transmitter
<b>Ambient temperature max. [°C]</b>	85 °C
<b>Ambient temperature max. [°F]</b>	185 °F
<b>Approval</b>	CE
<b>CE mark</b>	Yes
<b>China RoHS compliance</b>	Out of scope
<b>Connection material</b>	Stainless steel
<b>Connection standard</b>	ISO 228
<b>Connection type</b>	G
<b>Contains batteries</b>	No
<b>EEE category</b>	5 small equipment (any external dimension < 50 cm)
<b>Electrical conn. Male/Female</b>	Male and Female
<b>Electrical connection</b>	Angular connector
<b>Electrical connection size</b>	Pg 9
<b>Electrical connection standard</b>	EN 175301-803-A
<b>Enclosure rating IP</b>	IP65
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	6(c)
<b>In scope of WEEE</b>	Yes
<b>Insertion length [in]</b>	2.76 in
<b>Insertion length [mm]</b>	70 mm
<b>Insertion type</b>	Fixed
<b>Measuring range [°C] [max]</b>	150 °C
<b>Measuring range [°C] [min]</b>	-40 °C
<b>Measuring range [°F] [max]</b>	302 °F
<b>Measuring range [°F] [min]</b>	-40 °F
<b>Output signal [mA] [max]</b>	20 mA
<b>Output signal [mA] [min]</b>	4 mA
<b>Packing format</b>	Multi pack
<b>Process connection Male/Female</b>	Male
<b>Process connection material</b>	Stainless steel

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Temperature transmitter, MBT 3560, 70 mm, G,1/2**
**PRODUCT DETAILS**

<b>Process connection size</b>	1/2
<b>Process connection standard</b>	ISO 965
<b>Process connection type</b>	G
<b>Protection tube diameter [in]</b>	0.315 in
<b>Protection tube diameter [mm]</b>	8 mm
<b>Protection tube material</b>	AISI 316 TI
<b>Quantity per packing format</b>	13 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>SCIP dossier no.</b>	8127e7d9-3431-4421-a02a-bab746bc2e4f
<b>SCIP dossier product name</b>	Sensor MBT 3560
<b>Sensor elem. resistance [Ohm]</b>	1000 Ohm
<b>Sensor element [pc]</b>	1 pc
<b>Sensor element tolerance</b>	&lt;math>\pm 1\% \text{ FS}</math>
<b>Sensor element type</b>	Pt
<b>Sensor Insert</b>	Fixed
<b>Supply voltage [V] DC [max]</b>	32 V
<b>Supply voltage [V] DC [min]</b>	10 V
<b>Temperature range [°C] [max]</b>	200 °C
<b>Temperature range [°C] [min]</b>	-50 °C
<b>Temperature range [°F] [max]</b>	392 °F
<b>Temperature range [°F] [min]</b>	-58 °F
<b>Transmitter setting range [°C] [max]</b>	150 °C
<b>Transmitter setting range [°C] [min]</b>	-40 °C
<b>Transmitter setting range [°F] [max]</b>	302 °F
<b>Transmitter setting range [°F] [min]</b>	-40 °F
<b>Transmitter type</b>	Integrated
<b>Type designation</b>	MBT 3560-0001-0070-12-815

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)**

**Accessories**

**We're sorry, but the requested information is currently unavailable.**

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit [store.danfoss.com](https://store.danfoss.com).

Thank you for your understanding.

**For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.