



E2E-X4MB1T8-M5

Proximity sensor, inductive, short SUS body M8, unshielded, 4 mm, DC, 3-wire, PNP NO, IO-Link COM3, M8 connector 3 pins

Specifications

| | |
|---------------------------|----------------------|
| Size | M8 |
| Mounting type | Non-flush |
| Sensing distance | 4 mm |
| Overall length of sensor | 39 mm |
| Thread length | 20 mm |
| Material housing | Stainless steel |
| Output type | IO-Link, PNP |
| Operation mode | NO |
| Connection method | Connector M8 - 3 pin |
| Cable specifications | - |
| IO-Link function | ✓ |
| IO-Link baud rate | COM3 (230.4 kbps) |
| Degree of protection (IP) | IP67/IP69K |

Related products



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

CAD Library



E2E NEXT Datasheet

EN PDF 40 MB



E2E(Q) - Basic Models Index list

EN PDF 7.27 MB



E2E(Q) - Premium Models Index list

EN PDF 719 KB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 6.41 MB



XS5 NEXT Series Datasheet

EN PDF 2.39 MB