



S8VK-X12024A-EIP

Book type power supply, 120 W, 24 VDC, 5 A, DIN rail mounting, Push-in terminal, Coated, display, Ethernet IP / Modbus TCP compatibility

Specifications

Type	DIN-rail
Mounting method	DIN rail
Phase	Single
Output voltage	24 V
Power output	120 W
Efficiency	92 %
Rated output current	5 A
Power boost ratio	120 %
Temperature range	-40-70 °C
Features	Coated
Terminal type	Push-in
Communication port(s)	EtherNet/IP, MODBUS/TCP
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	55 mm
Product Height (unpacked)	94.7 mm
Product Depth (unpacked)	92.3 mm



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

Related products



S8V-NF
Noise Filter S8V-NF



Electronic Circuit Breaker
S8V-CP - Electronic Circuit Breaker

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Perfect Power Supply Solutions Brochure

EN PDF 1.29 MB



Power Supply Monitoring Tool Operation Manual

EN PDF 3.68 MB



Predictive Maintenance Solutions Vol.1 Flyer

EN PDF 4.01 MB



Predictive Maintenance Solutions Vol.2 Flyer

EN PDF 5.93 MB



Predictive Maintenance Solutions Vol.3 Flyer

EN PDF 3.35 MB



Predictive Maintenance Solutions Vol.4 Flyer

EN PDF 7.19 MB



Predictive Maintenance Solutions Vol.5 Flyer

EN PDF 3.96 MB



S8VK X Power Supply Monitoring Tool Software

EN ZIP 110 MB



S8VK-X Switch Mode Power Supply Communications Manual

EN PDF 1.23 MB



S8VK-X Switch Mode Power Supply Datasheet

EN PDF 6.54 MB



S8VK-X and NX PLC - Ethernet Communication Software

EN ZIP 2.01 MB



T235 Emea S8vk Series Switch Mode Power Supplies Brochure

EN PDF 1.75 MB