

# FL SFP WDM10-A - Media module



2702440

<https://www.phoenixcontact.com/gb/products/2702440>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Gigabit SFP WDM module for transmission up to a maximum of 10 km on a single fiber with a wavelength of 1310/1550 nm.

## Product description

SFP WDM module with a data transmission speed of 1000 Mbps, a wavelength of 1310/1550 nm, and a maximum transmission length of 10 km.

## Your advantages

- MSA compliant

## Commercial data

Item number	2702440
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNN1ZS
Product key	DNN1ZS
GTIN	4055626193854
Weight per piece (including packing)	36.3 g
Weight per piece (excluding packing)	33 g
Customs tariff number	85176200
Country of origin	TW

# FL SFP WDM10-A - Media module



2702440

<https://www.phoenixcontact.com/gb/products/2702440>

## Technical data

### Dimensions

Width	13.7 mm
Height	8.95 mm
Length	56.5 mm

### Notes

Note on application

Note on application	Only for industrial use
---------------------	-------------------------

### Material specifications

Housing material	Metal
------------------	-------

### Mounting

Mounting type	Plug-in mounting
Mounting type	Insert in SFP slot

### Interfaces

Ethernet FO

Connection method	LC
Transmission speed	1 Gbps
Transmit capacity, minimum	-9 dBm
Transmit capacity, maximum	-3 dBm
Minimum receiver sensitivity	-21 dBm
Maximum receiver sensitivity	0 dBm
Transmission physics	Single-mode fiberglass
Transmission length	10 km (Fiberglass 9/125)
Wavelength	1310 nm (TX) 1550 nm (RX)
Signal LEDs	depending on the Factoryline device
No. of channels	1 (LC single mode)

### Product properties

Type	Factoryline devices with SFP slot
MTTF	124 Years (Telcordia SR-332, temperature factor at 40°C = 1, stress factor at 50% = 1, environmental factor = 1)
Format	SFP (Small Form-factor Pluggable)

### Signaling

Status display	via a Factoryline device
----------------	--------------------------

### Electrical properties

# FL SFP WDM10-A - Media module



2702440

<https://www.phoenixcontact.com/gb/products/2702440>

Current consumption	300 mA
Maximum power dissipation for nominal condition	1 W
Transmission medium	FO

## Supply

Supply voltage	3.3 V (via Factoryline switch)
Power supply connection	via SFP slot
Max. current consumption	300 mA
Current consumption	300 mA

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C (non-condensing)
Case temperature	max. 85 °C (Operation)

## Standards and regulations

Standard designation	Laser equipment safety
Standards/specifications	IEC 60825

# FL SFP WDM10-A - Media module



2702440

<https://www.phoenixcontact.com/gb/products/2702440>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/2702440>



**DNV GL**

Approval ID: TAA00000YV



**LR**

Approval ID: LR22250919TA



**NK**

Approval ID: TA24215M



**BV**

Approval ID: 48146\_B1 BV

**BSH**

Approval ID: Nr. 966



**RINA**

Approval ID: ELE014724XG001

**ABS**

Approval ID: 21\_2066186\_1\_PDA



**cULus Recognized**

Approval ID: E140403

# FL SFP WDM10-A - Media module



2702440

<https://www.phoenixcontact.com/gb/products/2702440>

## Classifications

### ECLASS

ECLASS-13.0

19179090

### ETIM

ETIM 9.0

EC000310

### UNSPSC

UNSPSC 21.0

43222600

# FL SFP WDM10-A - Media module



2702440

<https://www.phoenixcontact.com/gb/products/2702440>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)