

fixed-mounted circuit breaker 3-pole, size I, IEC In=1000A to 690V, AC50/60Hz Icu=55kA at 500V frnt.conn. top/bot. single-hole Overcurrent release ETU 25 LSI protection adjustable 0.4-1 in Motorized/manual operating mechanism with spring charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC 50/60 Hz 230 V, 220 V DC without 1st auxiliary release With 2nd auxiliary release "RC", F4 Undervoltage, Delay 0.2-3.2s 208-240 V AC, 220-250 V DC, 100% ED 4NO+4NC

| Model | |
|---|---|
| product brand name | SENTRON |
| product designation | ACB |
| design of the product | IEC 60947-2 |
| design of the actuating element | Pushbutton |
| type of the driving mechanism | Manual/motorized operating mechanism with mechanical and electrical closing |
| design of the overcurrent release | ETU25B |
| General technical data | |
| size of the circuit-breaker | 1 |
| utilization category | B |
| circuit-breaker / Design | 3WL1 |
| Protection class | |
| protection class IP | IP20 |
| protection class IP / on the front | IP20 |
| protection function of the overcurrent release | LSI |
| Suitability | |
| suitability for use | Plant / motor protection |
| Product details | |
| design of the auxiliary switch | 4 NO + 4 NC |
| Display and operation | |
| display version | without display |
| Connections | |
| arrangement of electrical connectors / for main current circuit | Main connection top front/bottom single hole |
| type of electrical connection / for main current circuit | busbar connection |
| Mechanical Design | |
| fastening method | fixed mounting |
| Net Weight | 43 kg |
| Further information | |

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1110-2CB33-4AS4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1110-2CB33-4AS4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1110-2CB33-4AS4

CAx-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



