


LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG



- 1 LEDs
- 2 inductive programming button



Product characteristics	
Number of inputs and outputs	Number of digital outputs: 2
Factory setting	oils; oil-based media
Probe length L [mm]	132
Application	
Special feature	Gold-plated contacts
Media	Liquids
Dielectric constant of the medium	> 1,8
Recommended media	water; hydrous media; oils; oil-based media
Cannot be used for	See operating instructions, chapter "Intended use".
Medium temperature [°C]	-25...85; (applications subject to the German Federal Water Act 0...85°C)
Pressure rating	0.5 bar 0.05 MPa
Vacuum resistance [mbar]	-500
Electrical data	
Operating voltage [V]	9.6...35 DC; (IO-Link: 18...30 DC)
Current consumption [mA]	< 15
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	< 1
Measuring principle	capacitive
Inputs / outputs	
Number of inputs and outputs	Number of digital outputs: 2

LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG

Outputs		
Total number of outputs		2
Output signal		switching signal; IO-Link
Electrical design		PNP/NPN
Number of digital outputs		2
Output function	OUT-OP	normally closed
Output function	OUT2	normally open / normally closed; (parameterisable)
Max. voltage drop switching output DC [V]		2.5
Permanent current rating of switching output DC [mA]		100
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes
Measuring/setting range		
Factory setting		oils; oil-based media
Probe length L [mm]		132
Active range A [mm]		28
Temperature measurement		
Measuring range [°C]		-25...85
Accuracy / deviations		
Temperature measurement		
Accuracy [K]		1,5
Resolution [K]		0.1
Dynamic response T09 [s]		240
Response times		
Response time [s]		< 0.3
Interfaces		
Communication interface		IO-Link
Transmission type		COM2 (38,4 kBaud)
IO-Link revision		1.1
SDCI standard		IEC 61131-9
Profiles	Common - I&D	Identification and Diagnosis
SIO mode		yes
Required master port type		A
Process data analogue		5
Process data binary		2
Min. process cycle time [ms]		4.5
Supported DeviceIDs	Type of operation	DeviceID
	default	1588
Operating conditions		
Ambient temperature [°C]		-25...85
Storage temperature [°C]		-25...85

LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG

Protection	IP 68; IP 69K; (7 days / 3 m water depth / 0.3 bar: IP 68)
------------	------------------------------------------------------------

Tests / approvals

Approval	WHG; General building authority approval; overflow prevention; leakage detection	
EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	in a closed metal tank
	DIN EN 61000-6-4	in plastic or open metal tanks
Shock resistance	DIN EN 60068-2-27	12 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	5 g (10...2000 Hz)
MTTF [years]	433	
UL approval	UL approval no.	H013
	File number UL	E174191

Mechanical data

Weight [g]	240
Materials	PP reinforced fibre
Materials (wetted parts)	PP
Probe diameter [mm]	16

Displays / operating elements

Display	operation	LED, green
	switching status	LED, yellow
Operating elements	inductive programming button	

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated




LI2131



Sensor for point level detection

LI0132--K-00KQPKG/US/WHG

Connection



OUT-OP : IO-Link
switching output overflow prevention to the German Federal Water Act (WHG)
switching output leakage detection to WHG (German Federal Water Act)

OUT2 : switching output level
switching output temperature