



**131U6332**

**FC-302P1K5T5E20H2BXXXXXSSXXXALBXCXXXXDX**

Frequency converter  
 FC-302P1K5T5E20H2BXXXXXSSXXXALBXCXXXXDX  
 VLT® AutomationDrive FC-302  
 (P1K5) 1.5 KW / 2.0 HP, Three phase  
 380 - 500 VAC, (E20) IP20 / Chassis  
 RFI Filter  
 Brake chopper  
 No Loc. Cont. Panel  
 Not coated PCB, No Mains Option  
 Latest release std. SW.  
 Frame: A2  
 No C1 option, No D option  
 PROFINET MCA 120, No B Option  
 Other options according to Model code

**Model code:** FC-302P1K5T5E20H2BXXXXXSSXXXALBXCXXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

[View Efficiency Data](#)

**PRODUCT DETAILS**

<b>Gross weight</b>	4.54 kg	
<b>Net weight</b>	4.02 kg	
<b>Volume</b>	21.569 l	
<b>EAN</b>	5702427977853	
<b>VLT® AUTOMATIONDRIVE FC 300 SERIES</b>		
<b>Product View (Switch)</b>	GLBL	Global (Standard)
<b>Product Group</b>	FC-	VLT® AutomationDrive FC-
<b>Series</b>	302	302
<b>Power Rating</b>	P1K5	(P1K5) 1.5 KW / 2.0 HP
<b>Phase</b>	T	Three phase
<b>Mains Voltage</b>	5	380 - 500 VAC
<b>Enclosure</b>	E20	(E20) IP20 / Chassis
<b>RFI Filter</b>	H2	RFI Filter
<b>Brake - Safe Stop</b>	B	Brake chopper
<b>LCP</b>	X	No Loc. Cont. Panel
<b>Coating PCB</b>	X	Not coated PCB
<b>Mains Option</b>	X	No Mains Option
<b>Adaptation A</b>	X	Standard Cable Entries
<b>Adaptation B</b>	X	No adaptation
<b>Software Release</b>	SXXX	Latest release std. SW.
<b>Software Language Pack</b>	X	Standard Language Pack
<b>A Option</b>	AL	PROFINET MCA 120
<b>B Option</b>	BX	No B Option
<b>C0 Option MCO</b>	CX	No C0 option
<b>C1 Option</b>	X	No C1 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | FC-302P1K5T5E20H2BXXXXXALBXCXXXXDX

## PRODUCT DETAILS

<b>C Option Software</b>	XX	No software option
<b>D Option</b>	DX	No D option
<b>Frame Size</b>	A2	A2
<b>Typecode Part 1</b>		FC-302P1K5T5E20H2BXX
<b>Typecode Part 2</b>		XXXXXXXXALBXCXXXXDX
<b>Product Catalog</b>	NO_VIEW	NO VIEW
<b>Power 160% (HO) [KW]</b>		1.5
<b>Height [mm]</b>		268,0
<b>Width w/ no C options [mm]</b>		90,0
<b>Width w/ two C options [mm]</b>		150,0
<b>Depth [mm]</b>		205,0
<b>Depth with Option A/B [mm]</b>		220,0
<b>kVA</b>		2.84
<b>Power Loss HO [W]</b>		62
<b>Power Loss HO [W]</b>		62
<b>Continuous Current (HO) [A]</b>		4.1
<b>Intermittent Current (HO) [A]</b>		6.56
<b>Continuous Current (HO) [A]</b>		3.4
<b>Intermittent Current (HO) [A]</b>		5.44
<b>Calculated Gross Weight [kg]</b>		4.54
<b>Calculated Net Weight [kg]</b>		4.02
<b>ECCN EU</b>		Y901
<b>ECCN US</b>		3A999.a
<b>Vendor</b>	ERR01	Cannot Determine Vendor
<b>Recommended Factory</b>	ERR01	Cannot Determine Vendor
<b>Modelcode01</b>		FC-302P1K5T5E20H2BXX
<b>Modelcode02</b>		XXXXXXXXALBXCXXXXDX
<b>Recommended Plant</b>		ERR01

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

## Accessories



**130B7635** [🔗](#)

**VLT® Lift Controller MCO 361**

VLT® Motion Control MCO 305 with special software for lift application

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**130B7531** [🔗](#)**Mounting Kit f. C Option, 60mm, A2/A3**

VLT® Mounting kit for enclosure sizes A2 and A3.

Must be used when retrofitting 1 pc. of the following MCO options, together with MCB 113 Extended relay card (Located in MCO slot):

MCO 305 Programmable Motion Controller

MCO 350 Synchronizing Controller

MCO 351 Positioning controller

MCO 360 Salt Controller

MCO 361 Lift Controller

Product group: R

---

**130B7530** [🔗](#)**Mounting Kit f. C Option, 40mm, A2/A3**

MCF 105 assembly kit A2 / A3 for C option

---

**130B7389** [🔗](#)**NEMA 1 Conversion Kit, Top, 10 pcs, A2**

---

**130B7145** [🔗](#)**VLT® SALT Controller MCO 360**

---

**130B5645** [🔗](#)**Leakage Current Monitor Kit, A2, A3**

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**130B1234** **VLT® Motion Control MCO 305, coated**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

- 8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus option)
- PC software for programming and commissioning

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

**130B1227** **VLT® Resolver Input MCB 103, coated**

Resolver extension for FC 300. Enables the connection of the following

Resolver types:

Input voltage: 4..8 Vrms

Input frequency: 2.5..15 kHz

Number of resolver poles: 2 or 4

**130B1220** **VLT® Safe PLC I/O MCB 108, coated**

Increases security and helps you meet requirement security levels

- VLT® AutomationDrive FC 302 has a safety input based on a single pole 24 V DC input
- Security in a cost-effective way

Possibility of connection to two conductor safety system

Possibility to interrupt on the plus or minus side without disturbing the sensor signal

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B1264** [🔗](#)

**VLT® Extended Relay Card MCB 113, ctd**

Adds 7 digital inputs and 2 analog outputs for increased flexibility. 4 SPDT relays. Meets NAMUR recommendations. Galvanic isolation capability.



**130B1253** [🔗](#)

**VLT® Position Controller MCO 351, ctd**

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning
- End stop handling (software and hardware)
- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation
- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R



**130B1252** [🔗](#)

**VLT® Synchronizing Ctrl. MCO 350, ctd**

MCO 350 - synchronous controller

Based on the MCO 305 prefabricated controller for Synchronization tasks. The adjustment takes place through parameter settings. Specific Programming skills are not required.

- 2 encoder inputs, both for incremental as well as absolute encoder
- 1 encoder output (virtual master function)
- 10 additional digital inputs
- 8 additional digital outputs
- fieldbus Communication (requires fieldbus card) with reinforced coating



**130B1172** [🔗](#)

**VLT® Sensor Input Card MCB 114, unctd**

Protects the motor from being overheated by monitoring the temperature of bearings and windings in the motor. Three self-detecting sensor inputs for 2 or 3 wire PT100/PT1000 sensors. One additional analog input 4–20 mA.

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B1170** [🔗](#)

**LCP Panel Mounting Kit**

The kit includes fasteners and gasket. No LCP and no cable included.



**130B1212** [🔗](#)

**VLT® General Purpose I/O MCB 101, ctd**

MCB 101 - Advanced I / O option

Expands the number of freely programmable

Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
  - 2 analog inputs 0 - 10 V.
  - 2 digital outputs NPN / PNP switchable 24 V
  - 1 analog output 0/4 - 20 mA
- with reinforced coating



**130B1210** [🔗](#)

**VLT® Relay Option MCB 105, coated**

Relay extension for FC 100 and FC 300.

Extension with 3 additional load relays (changeover contacts),  
easy to retrofit thanks to modular technology.

Painted version for harsh environments,  
easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A



**130B1208** [🔗](#)

**1xMCB 107 24V DC coat w. mount. brackets**

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.



**130B1203** [🔗](#)

**VLT® Encoder Input MCB 102, coated**

Offers the possibility to connect various types of incremental and absolute encoders. The connected encoder can be used for closed-loop speed control as well as closed-loop flux motor control.



**130B1387** [🔗](#)

**5xMCB107 24VDC no coat w.out mount brack**

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

**130B1383** [🔗](#)**acc. bag multipack 5 pc frame A2/3**

Kroner acc. bag multipack 5pcs for A2/3-frame.

**130B1272** [🔗](#)**VLT® Sensor Input Card MCB 114, coated**

MCB 114 - PT100 / PT1000 option

For FC100-FC200 and FC302 (painted version)

Enables the evaluation of up to 3 PT 100 or 3 PT 1000 sensors

- Connection of 2 and 3 wire sensors
- Automatic detection of the sensor type
- Additional 4-20mA input

**130B1164** [🔗](#)**VLT® Extended Relay Card MCB 113**

Adds 7 digital inputs and 2 analog outputs for increased flexibility. 4

SPDT relays. Meets NAMUR recommendations. Galvanic isolation capability.

**130B0185** [🔗](#)**Adapter Plate, 395x220mm**

With the adapter plate you can replace a VLT® 5/6/8000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 5/6/8000, and as there will be no drilling there will be no swarf harming the electric components.

The following VLT® 5/6/8000 can be mounted on the Adapter Plate 130B0185:

IP20 Compact: 200-240Volt VLT5001-5006, 380/500Volt VLT5001-5011

IP20/NM1: 200-240Volt VLT6002-6005, 380/460Volt VLT6002-6011, 380-480Volt VLT8006-8011, 550-600Volt VLT 5001-5011, 525-690Volt VLT8002-8011

**130B0184** [🔗](#)**Adapter Plate, 395x130mm**

With the adapter plate you can replace a VLT® 5/6/8000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 5/6/8000, and as there will be no drilling there will be no swarf harming the electric components.

The following VLT® 5/6/8000 can be mounted on the Adapter Plate 130B0184:

IP20 Book: 200-240Volt VLT5004-5006/VLT6004-6005, 380/500Volt VLT5006-5011,

380-460Volt VLT6006-6011

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B0183**

**Adapter Plate, 395x90mm**

With the adapter plate you can replace a VLT® 5/6/8000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 5/6/8000, and as there will be no drilling there will be no swarf harming the electric components. The following VLT® 5/6/8000 can be mounted on the Adapter Plate 130B0183:  
IP20 Book: 200-240Volt VLT5001-5003/VLT6002-6003, 380/500Volt VLT5001-5005, 380-460Volt VLT6002-6005



**130B0056**

**Adapter Plate, 338x279mm**

With the adapter plate you can replace a VLT® 3000 by a FC drive without having to drill new holes for the FC drive. This makes it easy and fast to replace a VLT® 3000, and as there will be no drilling there will be no swarf harming the electric components. It is possible to install one or two FC drives in the same place as one VLT® 3000. Or one FC drive with a full size C Option (e.g. MCO305). The following VLT® 3000 can be mounted on the Adapter Plate 130B0056:  
IP00/21: 220/380/500Volt VLT3002-3004 with no brake



**130B1134**

**VLT® Motion Control MCO 305, uncoated**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs  
8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus Option)
- PC software for programming and commissioning.

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3  
130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3.  
130B1413 - Mounting kit for enclosure B3  
130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3  
130B7532 - Mounting kit for enclosure A5  
130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.  
Product group: R



**130B1132**

**IP 21/Type 1 conversion kit, top, A2**

This is only the top part of the kit - If you need a kit with both top and bottom please order 130B1122

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B1127** [🔗](#)

**VLT® Resolver Input MCB 103, uncoated**

Enables connection of a resolver to provide speed feedback from the motor. Spring loaded connection.



**130B1125** [🔗](#)

**VLT® General Purpose I/O MCB 101, unctd**

MCB 101 - Advanced I / O option

Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
- 2 analog inputs 0 - 10 V.
- 2 digital outputs NPN / PNP switchable 24 V
- 1 analog output 0/4 - 20 mA



**130B1124** [🔗](#)

**VLT® Control Panel LCP 101, numeric**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters. Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.



**130B1122** [🔗](#)

**IP 21/Type 1 conversion kit, A2**

Cover for housing size A2 MCF 101 NEMA1 / IP21



**130B1120** [🔗](#)

**VLT® Safe PLC I/O MCB 108, uncoated**

Connection converter for FC 300 with control input for a safe stop. Allows secure connection. Output modules with diagnostic pulse (Cross-circuit monitoring).



**130B1117** [🔗](#)

**LCP Mounting Kit, w/ no LCP**

The kit includes fasteners, 3m cable and gasket - There is no LCP included.



**130B1115** [🔗](#)

**VLT® Encoder Input MCB 102, uncoated**

Offers the possibility to connect various types of incremental and absolute encoders. The connected encoder can be used for closed-loop speed control as well as closed-loop flux motor control.



**130B1114** [🔗](#)

**LCP Mounting Kit w/ numerical LCP101, 3m**

The kit includes numerical LCP, fasteners, 3m cable and gasket.

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories



### 130B1113 [🔗](#)

#### lcp panel kit/fc300 fg-lcp panel kit

The kit includes graphical LCP, fasteners, 3m cable and gasket.



### 130B1110 [🔗](#)

#### VLT® Relay Option MCB 105, uncoated

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A



### 130B1153 [🔗](#)

#### VLT® Position Controller MCO351, unctd

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning

- End stop handling (software and hardware)

- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation

- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R



### 130B1152 [🔗](#)

#### VLT® Synchronizing Contr. MCO350, unctd

Expands the functional properties of the VLT® AutomationDrive in synchronizing applications, and replaces traditional mechanical solutions. Speed synchronizing. Position (angle) synchronizing with or without marker correction. Online adjustable gear ratio. Online adjustable position (angle) offset. Encoder output with virtual master function for synchronization of multiple followers. Control via I/Os or fieldbus. Home function. Configuration as well as read-out of status and data via the Local Control Panel of the drive.

**For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**130B1137** [🔗](#)

**VLT® PTC Thermistor Card MCB 112, ctd**

MCB 112 PTC - thermistor relay MS220DA In connection with ATEX certified explosion-proof motors for full motor protection. Certified PTC sensors are the sole protection required.

Integrable module with ATEX-compliant full thermal motor protection

1 PTB-certified PTC thermistor input

1 switch-off signal for using the Safe Stop function

1 logic output for error identification



**130B1077** [🔗](#)

**Blindcover, w/ Danfoss logo, IP55/66**

LCP Blindcover IP66



**130B1071** [🔗](#)

**6 Pole Connector, FC series, 10 pcs**

6-pole spring cage connectors 10 pcs



**130B1070** [🔗](#)

**RS485 plug, FC series, 10 pcs**

10pcs RS485 connectors for FC-series.

Product group: R



**130B1108** [🔗](#)

**VLT® 24V DC Supply MCB 107, uncoated**

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.



**130B1107** [🔗](#)

**VLT® Control Panel LCP 102**

Graphic operating unit LCP102 Illuminated graphic display with plain text. Supports all languages and characters. Quick menu for brief commissioning. Saving and copying parameter sets. Online help for each function



**130B1088** [🔗](#)

**LCP Blindcover, w/ Danfoss logo, IP20/21**



**175U0087** [🔗](#)

**Mount. Brack. Footprint, A2, f. 2 br.res**

Back frame A2 for 2 brake resistors

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**175U0085** [↗](#)**Mounting bracket: Footprint, A2**

Back frame A2 for 1 brake resistor

Image  
coming  
soon**175U0388** [↗](#)**Mounting brackets: Footprint, K3****175Z0929** [↗](#)**LCP Cable, 3m**

Cable for control panel (LCP), 3 meters

Works with the following LCP:

Alphanumeric control panel LCP3 - 175N0131

VLT® LCP 102 Graphic Display - 130B1107

VLT® LCP 101 Numeric Display - 130B1124

VLT® LCP 102 Graphic display IP66 - 130B1078

Product group: F1

Image  
coming  
soon**175U0009** [↗](#)**Mounting bracket Kit, 216 x 30 x 18mm**

Mounting angle for flatpack resistor 200W

**175N2584** [↗](#)**VLT® EtherNet/IP Modbus TCP gateway**Image  
coming  
soon**134B5225** [↗](#)**Remote LCP unit, 10m**Remote mounting kit for LCP with cover for outdoor mounting with 10 m  
(33 ft) cableImage  
coming  
soon**134B5224** [↗](#)**Remote LCP unit, 5m**Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16  
ft) cable**134B5223** [↗](#)**Remote LCP unit, 3m**Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10  
ft) cable**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**134B0460**

**LCP 103 Wireless Communication Panel**

With VLT® Wireless Communication Panel LCP 103 you can communicate with MyDrive® Connect - an app that can be downloaded for iOS and Android based smartphones. MyDrive® Connect makes commissioning easy, monitor and maintain tasks on your frequency converter. VLT® Wireless Communication Panel LCP 103 shows the current status of the drive (On, Warning, Alarm, Wifi connection) via built-in LED. Detailed information is also available using MyDrive® Connect. Here do you have access to i.a. status, menu and alerts. You can also see graphs over the latest available data.

The new VLT® Wireless Communication Panel LCP 103 allows you to wireless communication to the following drives:

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302

[!] Note!

LCP 103 only works on frequency converters produced in 2018 (White USB stik).

Product group: R1

Image coming soon

**134B1992**

**Control Terminals w/ screw connections**



**130B1266**

**VLT MCB 115 Programmable I/O, coated**

VLT® MCB 115 programmable I / O, coated



**134B6544**

**Real Time Clock D slot option MCB117**

The VLT® Real-time clock option MCB 117 option provides advanced data-logging functionality to the following drives

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® Aqua Drive FC 202
- VLT® Automation Drive FC 301/FC 302

Note: This option is compatible only with MK-II control cards & upto 90 KW supporting A,B & C Frames.



**130B0295**

**sparepart/terminals accessory bag**



**130B1022**

**fc-300 spare part/acc. bag a2 +a3 encl.**

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

Image  
coming  
soon**134B1976** [🔗](#)**Accessory bag for frame A1-A3 w. brake**Image  
coming  
soon**130B4847** [🔗](#)**extension cable for lcp+communication****134B8492** [🔗](#)**Transducer 0-10g, 4-20mA; HS-22B50****134B8493** [🔗](#)**Transducer 0-25mm/s RMS 4-20mA**

CBM Transducer 0-25mm/s RMS 4-20mA

**134B8494** [🔗](#)**Transducer w, temp 0-25mm/s RMS 4-20mA****134B8496** [🔗](#)**CABLE ASSY 10M, STRAIGHT SOCKET CONNETC.**Image  
coming  
soon**134B8497** [🔗](#)**Cable assy, M12 female connec.10m screen**Image  
coming  
soon**134B6883** [🔗](#)**VLT Progr. Contr. MCB 301, coated****For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**134B9414** **Antifreeze Thermostat FS20, 0/+15C**

TWO-PHASE FROST PROTECTION THERMOSTATS FS-20-UW

Electronic frost protection thermostat or frost monitor with switching relay output, continuous temperature and valve output (summation output 0–10 V) and control and cascading output (0–10 V), optionally with connection for a heating element. A IP65 resistant plastic housing with display with the actual temperature, measuring range, overrange/underrange of the set switch point (frost protection temperature) and alarm indicator for "frost" or "error" (capillary breakage, overvoltage/undervoltage), quick-locking screws and a fully active sensor rod made of copper. The delivery scope includes a set of MK-05-K mounting clamps for expert attachment of the sensor rod.

Measuring range: 0...+15 °C / 32...+59 °F

Accuracy: typical ± 1 K (at +10 °C)

Sensor type: 3m Copper rod active along the entire sensor length, min. response length of 25 cm

Input: 1 x 0 -10 V control input DDC &amp; 1 x 0 -10 V cascading input

Output: 1 x 0 -10 V output temperature (corresponding to 0...+15 °C) &amp; 1 x 0 -10 V output valve (frost signal with control voltage and cascading)

1 x potential-free changeover contact (24 V), range of adjustment 0...+15 °C

Current consumption: max. 100 mA at 24 V DC

Load resistance:  $R_L > 50 \text{ k}\Omega$ 

Ambient temperature: -15...+50 °C / 5...+122 °F (Housing) &amp; -20...+60 °C / -4...+140 °F Sensor and capillary tube &gt; 20 cm from the housing.

Power: 24VAC/DC (± 10%) 24DC &lt;2,4W

T2-IP65 plastic housing with three-line display 70x40 mm (WxH), a M16 cable glands and MK-05-K mounting clamps.

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**


---

**134B9413** **Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas & selection of VOC sensitivities (low/medium/high)

VOC measuring accuracy: typical  $\pm 20\%$  of final value (referred to calibrating gas)

CO2 Sensor: optical NDIR sensor (non-dispersive infra-red technology) including atmospheric pressure compensation (up to 1100 mbar) with manual or automatic calibration

CO2 measuring range: 0...5000 ppm

CO2 measuring accuracy: typical  $\pm 30$  ppm ( $\pm 3\%$  of measured value) & temperature dependence:  $\pm 5$  ppm pro  $^{\circ}\text{C}$  or  $\pm 0,5\%$  of measured value pro  $^{\circ}\text{C}$  (whichever is higher) & pressure dependence:  $\pm 0.13\%$  per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ( $\pm 10\%$ ) 24DC  $<1,6\text{W}$

Operation temperature:  $-10...+60\text{ }^{\circ}\text{C}$  /  $14...+140\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**


---

**134B9412** [🔗](#)**Airflow Sensor TF65 PT1000 Temperature**

DUCT TEMPERATURE SENSOR TF 65

The TF 65 temperature measuring transducer is a PT1000 class B resistance sensor with passive output. Measuring range from  $-30...+150^{\circ}\text{C}$ . In a resistant IP67 plastic housing and M16 cable gland for cable connection and a straight protective measuring tube and a mounting flange.

Sensor type: PT1000 class B (DIN EN 60751) 1000ohm at  $0^{\circ}\text{C} \pm 0,3\text{ K}$ Measuring range:  $-30...+150^{\circ}\text{C}$  /  $-22...+302^{\circ}\text{F}$ Ambient temperature:  $-20...+100^{\circ}\text{C}$  /  $-4...+212^{\circ}\text{F}$ Testing current:  $< 0,6\text{ mA}$ Insulating resistance: 100 M#, at  $+20^{\circ}\text{C}$  (500V DC)

Connection type: 2-wire connection

Measuring tube: stainless steel, V4A (1.4571),  $\varnothing 6\text{ mm}$ , inserted length = 300 mm / 11.8 in

T1-IP67 plastic housing with a M16 cable glands and a mounting flange.

Housing dimensions: 72 x 64 x 37.8 mm / 2.83 x 2.52 x 1.49 in

**134B9411** [🔗](#)**Wall Sensor AFTF Temp & Humidity**

ON-WALL- HUMIDITY- AND TEMPERATURE SENSORS AFTF-MB

Calibratable outside humidity and temperature sensor AFTF, detect the relative humidity (0...100% RH) and the temperature ( $-35...+80^{\circ}\text{C}$ ), including various parameters in the humidity measurement. Applied in clean air and non-aggressive, dust-free environment. With a Modbus connection in a resistant IP65 plastic housing and M20 cable gland for cable connection, with quick-locking screws and an exchangeable plastic sinter filter. International SI units (default) can be changed to imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) /  $-35...+80^{\circ}\text{C}$  (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical  $\pm 2,0\%$  (20...80 % RH) at  $+25^{\circ}\text{C}$ , otherwise  $\pm 3,0\%$ Deviation, temperature: typical  $\pm 0,4\text{ K}$  at  $+25^{\circ}\text{C}$  /  $\pm 77^{\circ}\text{F}$ Zero point offset:  $\pm 10\%$  RH (humidity) /  $\pm 5^{\circ}\text{C}$  (temperature)Power: 24VAC ( $\pm 20\%$ ) / 15...36VDC - 24DC  $< 1,2\text{W}$ Operation temperature:  $-30...+70^{\circ}\text{C}$  /  $-22...+158^{\circ}\text{F}$ 

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

**134B9410****Wall Sensor ATM2 Temperature**

OUTSIDE / WET ROOM TEMPERATURE SENSOR ATM2-MB

Calibratable outside temperature sensor ATM2, PT1000 measure temperature (-50...+150 °C), with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M20 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

Sensor type: PT1000 class B (DIN EN 60751)

Measuring range: - 50...+150°C / -31... +176°F

Deviation: typical ± 0.2 K at +25 °C / ± 77 °F

Zero point offset: ± 10 °C / ± 50 °F

Ambient temperature: Measuring transducer -30...+70 °C / -22... +158°F

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;1,2W

Operation temperature: -30...+70 °C / -22...+158 °F

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

Image  
coming  
soon**134B9409****Airflow Sensor 8147 Temp&Humidity&7000Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±7000PA-MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 7000 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80°C / -31... +176°F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F , otherwise ± 3.0 %

Deviation, temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F

Pressure range: ± 7000 Pa

Accuracy: 7000 Pa/28 inWC: typical ± 105 Pa at +25 °C / ± 0.12 inWC at +77 °F

Above- # below-pressure: max. ± 50 kPa

Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;0,2W

Operation temperature: -30...+70 °C / -22...+158 °F

Media temperature -20...+50 °C / -4...+122 °F IP65 plastic housing two

M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

Image  
coming  
soon**134B9408** **Airflow Sensor 8148 Temp&Humidity&500Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS  $\pm 500$ PA-MB  
Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ( $-35...+80$  °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max.  $\pm 500$  Pa) with connection nozzles for pressure hose ( $\varnothing 6$  mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) /  $-35...+80$ °C /  $-31...+176$ °F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical  $\pm 2.0$  % (20...80 % RH) at  $+25$ °C/ $+77$ °F, otherwise  $\pm 3.0$  %

Deviation, temperature: typical  $\pm 0.2$  K at  $+25$  °C /  $\pm 0.4$  °F at  $+77$  °F

Pressure range:  $\pm 500$  Pa

Accuracy: 500 Pa/2.0 inWC: typical  $\pm 13$  Pa at  $+25$  °C /  $\pm 0.05$  inWC at  $+77$  °F

Above- # below-pressure: max.  $\pm 50$  kPa

Power: 24VAC ( $\pm 20$ %) / 15...36VDC - 24DC  $<0,2$ W

Operation temperature:  $-30...+70$  °C /  $-22...+158$  °F

Media temperature  $-20...+50$  °C /  $-4...+122$  °F IP65 plastic housing two

M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Accessories

**134B9407** [🔗](#)**Airflow Sensor KFTF Temp & Humidity**

DUCT HUMIDITY- AND TEMPERATURE SENSORS KFTF-MB

Calibratable duct humidity and temperature sensor KFTF-T3 ( $\pm 2.0\%$ ) with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection and a plastic sinter filter (exchangeable). Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ( $-35...+80\text{ }^{\circ}\text{C}$ ) inside a tube, including various parameters in the humidity measurement. The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices.

International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) /  $-35...+80\text{ }^{\circ}\text{C}$  (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical  $\pm 2.0\%$  (20...80 % RH) at  $+25\text{ }^{\circ}\text{C}$ , otherwise  $\pm 3.0\%$

Deviation, temperature: typical  $\pm 0.2\text{ K}$  at  $+25\text{ }^{\circ}\text{C}$

Zero point offset:  $\pm 10\%$  RH (humidity) /  $\pm 5\text{ }^{\circ}\text{C}$  (temperature)

Power: 24VAC ( $\pm 20\%$ ) / 15...36VDC - 24DC  $<1,2\text{ W}$

Operation temperature:  $-30...+70\text{ }^{\circ}\text{C}$  /  $-22...+158\text{ }^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

**134B9406** [🔗](#)**Pressure Sensor 7227 2x7000Pa, Analog**DUAL AIR PRESSURE SENSOR  $\pm 7000\text{ Pa}$  &  $\pm 7000\text{ Pa}$ , ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing 6\text{ mm}$ ) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0-10 V or 4...20 mA.

Pressure range selection:  $\pm 7000\text{ Pa}$  - 0...1000Pa / 2000Pa / 3000Pa / 5000Pa / 7000Pa

Accuracy: 7000 Pa typical  $\pm 105\text{ Pa}$

Zero point offset:  $\pm 10\%$  of measuring range

Above- # below-pressure: max.  $\pm 50\text{ kPa}$

Power: 24VAC/DC ( $\pm 10\%$ )  $<1,3\text{ W}$ ,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance:  $R_a$  (ohms) = 25...450 Ohm (at I output)

Load resistance:  $R_L > 15\text{ kOhm}$  (at U output)

Operation / Media temperature:  $-20...+50\text{ }^{\circ}\text{C}$  /  $-4...+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**


---

**134B9405** **Pressure Sensor 7229 500/7000Pa, Analog**DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$  &  $\pm 7000\text{Pa}$ , ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing$  6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection:  $\pm 500\text{ Pa} - 0...100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$  Pressure range selection:  $\pm 7000\text{ Pa} - 0...1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$

Accuracy: 500 Pa typical  $\pm 13\text{ Pa}$ Accuracy: 7000 Pa typical  $\pm 105\text{ Pa}$ Zero point offset:  $\pm 10\%$  of measuring rangeAbove- # below-pressure: max.  $\pm 50\text{ kPa}$ Power: 24VAC/DC ( $\pm 10\%$ )  $< 1,3\text{W}$ ,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance:  $R_a$  (ohms) = 25...450 Ohm (at I output)Load resistance:  $R_L > 15\text{ kOhm}$  (at U output)Operation / Media temperature:  $-20...+50\text{ }^\circ\text{C} / -4...+122\text{ }^\circ\text{F}$ 

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9404** **Pressure Sensor 7225 2x500Pa, Analog**DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$  &  $\pm 500\text{Pa}$ , ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing$  6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection:  $\pm 500\text{ Pa} - 0...100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$

Accuracy: 500 Pa typical  $\pm 13\text{ Pa}$ Zero point offset:  $\pm 10\%$  of measuring rangeAbove- # below-pressure: max.  $\pm 50\text{ kPa}$ Power: 24VAC/DC ( $\pm 10\%$ )  $< 1,3\text{W}$ ,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance:  $R_a$  (ohms) = 25...450 Ohm (at I output)Load resistance:  $R_L > 15\text{ kOhm}$  (at U output)Operation / Media temperature:  $-20...+50\text{ }^\circ\text{C} / -4...+122\text{ }^\circ\text{F}$ 

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**


---

**134B9402** **Pressure Sensor 7247T 2x7000Pa & PT1000**DUAL AIR PRESSURE SENSOR  $\pm 7000\text{Pa}$  &  $\pm 7000\text{Pa-MB}$ 

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ( $-50\dots+150^\circ\text{C}$ ). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing 6\text{ mm}$ ) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range:  $\pm 7000\text{ Pa}$  and  $\pm 7000\text{ Pa}$ Accuracy: 7000 Pa/28 inWC: typical  $\pm 105\text{ Pa}$  at  $+25^\circ\text{C}$  /  $\pm 0.12\text{ inWC}$  at  $+77^\circ\text{F}$ Linearity:  $< \pm 1\%$  of final value & Temperature drift:  $\pm 0.1\%$  per  $^\circ\text{C}$  #  
 $^\circ\text{F}$ Zero point offset:  $\pm 10\%$  of measuring rangeAbove- # below-pressure: max.  $\pm 50\text{ kPa}$  /  $\pm 200\text{ inWC}$ Power: 24VAC ( $\pm 20\%$ )  $< 0,2\text{W}$  / 15...36VDCOperation temperature:  $-30\dots+70^\circ\text{C}$  /  $-22\dots+158^\circ\text{F}$ Media temperature  $-20\dots+50^\circ\text{C}$  /  $-4\dots+122^\circ\text{F}$ 

T2-IP65 plastic housing with two M16 cable glands &amp; one M12 for temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9401** **Pressure Sensor 7249T 500/7000Pa & PT1000**DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$  &  $\pm 7000\text{Pa-MB}$ 

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ( $-50\dots+150^\circ\text{C}$ ). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing 6\text{ mm}$ ) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range:  $\pm 500\text{ Pa}$  and  $\pm 7000\text{ Pa}$ Accuracy: 500 Pa/2.0 inWC: typical  $\pm 13\text{ Pa}$  at  $+25^\circ\text{C}$  /  $\pm 0.05\text{ inWC}$  at  $+77^\circ\text{F}$ Accuracy: 7000 Pa/28 inWC: typical  $\pm 105\text{ Pa}$  at  $+25^\circ\text{C}$  /  $\pm 0.12\text{ inWC}$  at  $+77^\circ\text{F}$ Linearity:  $< \pm 1\%$  of final value & Temperature drift:  $\pm 0.1\%$  per  $^\circ\text{C}$  #  
 $^\circ\text{F}$ Zero point offset:  $\pm 10\%$  of measuring rangeAbove- # below-pressure: max.  $\pm 50\text{ kPa}$  /  $\pm 200\text{ inWC}$ Power: 24VAC ( $\pm 20\%$ )  $< 0,2\text{W}$  / 15...36VDCOperation temperature:  $-30\dots+70^\circ\text{C}$  /  $-22\dots+158^\circ\text{F}$ Media temperature  $-20\dots+50^\circ\text{C}$  /  $-4\dots+122^\circ\text{F}$ 

T2-IP65 plastic housing with two M16 cable glands &amp; one M12 for temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**134B9400** **Pressure Sensor 7245T 2x500Pa & PT1000**DUAL AIR PRESSURE SENSOR  $\pm 500\text{Pa}$  &  $\pm 500\text{Pa-MB}$ 

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ( $-50\dots+150^\circ\text{C}$ ). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ( $\varnothing 6\text{ mm}$ ) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range:  $\pm 500\text{ Pa}$  and  $\pm 500\text{ Pa}$ Accuracy:  $500\text{ Pa}/2.0\text{ inWC}$ : typical  $\pm 13\text{ Pa}$  at  $+25^\circ\text{C}$  /  $\pm 0.05\text{ inWC}$  at  $+77^\circ\text{F}$ Linearity:  $< \pm 1\%$  of final value & Temperature drift:  $\pm 0.1\%$  per  $^\circ\text{C}/^\circ\text{F}$ Zero point offset:  $\pm 10\%$  of measuring rangeAbove-/below-pressure: max.  $\pm 50\text{ kPa}$  /  $\pm 200\text{ inWC}$ Power:  $24\text{VAC}$  ( $\pm 20\%$ )  $< 0,2\text{W}$  /  $15\dots 36\text{VDC}$ Operation temperature:  $-30\dots+70^\circ\text{C}$  /  $-22\dots+158^\circ\text{F}$ Media temperature  $-20\dots+50^\circ\text{C}$  /  $-4\dots+122^\circ\text{F}$ 

T2-IP65 plastic housing with two M16 cable glands &amp; one M12 for temperature

Housing dimensions:  $126 \times 90 \times 50\text{ mm}$  /  $4.96 \times 3.54 \times 1.97\text{ in}$ **130B5601** **VLT® DeviceNet converter MCA194 coated**

VLT® DeviceNet converter MCA194 coated

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.