

Pointek CLS300 RF Capacitance point level switch, rod design. Detects level and interface in aggressive liquids, solids, slurries, and foam. Adjustable, 1 m (3.28 ft), insertion, adaptable sensitivity, with active shield to tune out build-up on probe. Process Connection: Threaded, 316L (1.4404) stainless steel 1 1/2" NPT (Taper), ANSI/ASME B1.20.1 Probe length: (length from flange face) (threaded lengths include process thread) Add order code Y01 and plain text: "Insertion length ... mm" Extended rod, factory adjusted length 500 to 749 mm (19.69 to 29.49") Thermal Isolator: With thermal isolator (for process connection temperatures over +85 C (+185 F)) Wetted Seals: FKM Probe Material: 316L Stainless Steel with PFA lining and PEEK Isolators Approvals: General Purpose (CSA, FM) Enclosure and Lid: Aluminum epoxy coated 2 x 1/2" NPT via adapter - cable inlet, IP65 Active Shield Length: Standard length - (125 mm threaded, 105 mm flanged) Manufacturer's Test Certificate: M to DIN 55350, Part 18 and to ISO 9000 Total insertion length: Enter the total insertion length in plain text description. Total insertion length xxxx mm

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

