



G7SA-2A2B 24VDC

Safety relay, plug-in, DPST-NO, DPST-NC, 6 A, forcibly-guided contacts, 24 VDC

Specifications

Number of contacts, normally-open	2
Number of contacts, normally-closed	2
Coil voltage	24 V
Rated carry current	6 A
Features	Transparent case, With forced-guided contacts

Accessories



P7SA-10F

Socket, DIN rail/surface mounting, 10-pin, screw terminals, for G7SA 4 pole relays



P7SA-10F-ND 24VDC

Socket, DIN rail/surface mounting, 10 pin, screw terminals, for G7SA 4 pole relays, LED indicator



P7SA-10F-ND-PU 24VDC

Socket, DIN rail/surface mounting, 10 pin, push-in terminals, for G7SA 4 pole relays, LED indicator



P7SA-10P

Socket, back connecting, PCB terminals, 10-pin, for G7SA 4 pole relays

Related products



P7SA

G7SA safety relays family sockets range

Downloads


CAD Library



G7SA Relays with Forcibly Guided Contacts

Datasheet

EN PDF 3.22 MB



Machine Safety Catalogue

EN PDF 9.91 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



Safety Component Selection Guide EU

Brochure

EN PDF 5.26 MB



Safety Solution Advanced Guide

Guide

EN PDF 2.57 MB



Safety Solution Basic Guide

Guide

EN PDF 14.4 MB



Snabbguide G7SA-reläer

Leaflet

SV PDF 235 KB

