


Product datasheet

Specifications



Motor Management, TeSys T, motor controller, CANopen, 6 logic inputs, 3 relay logic outputs, 5 to 100A, 100 to 240 VAC

Local distributor code:

389823005

LTMR100CFM

EAN Code: 3389119404730

Main

Range	TeSys
Product name	TeSys T
Device short name	LTMR
Product or component type	Motor controller
Device application	Equipment monitoring and control
Measurement current	5...100 A
[Us] rated supply voltage	100...240 V AC 50/60 Hz
Current consumption	8...62.8 mA
Supply voltage limits	93.5...264 V AC
Communication port protocol	CANopen
Bus type	CANopen ISO 1198 interface, addressing 1...127, transmission rate 10...1000 kbit/s, SUB-D 9 with 4 twisted shielded pairs cable CANopen ISO 1198 interface, addressing 1...127, transmission rate 10...1000 kbit/s, terminal block with 4 twisted shielded pairs cable

Complementary

[Ui] rated insulation voltage	690 V conforming to EN/IEC 60947-1 690 V conforming to CSA C22.2 No 14 690 V conforming to UL 508
[Uimp] rated impulse withstand voltage	4 kV supply, inputs and outputs conforming to EN/IEC 60947-4-1 6 kV current or voltage measurement circuit conforming to EN/IEC 60947-4-1 0.8 kV communication circuit conforming to EN/IEC 60947-4-1
Short-circuit withstand	100 kA conforming to EN/IEC 60947-4-1
Associated fuse rating	4 A gG for output 0.5 A gG for control circuit
Protection type	Thermal protection Locked rotor Phase failure Earth-leakage protection Overload (long time) Power factor variation Phase unbalance Load fluctuation Thermal overload protection Reverse polarity protection Overload

Network and machine diagnosis type	Event recording Trip history information Starting current and time Running hours counter/operating time Motor control command recording Remaining operating time before overload tripping Fault recording Phase fault and earth fault trip counters Waiting time after overload tripping Trip context information
Logic input number	6
Input current	3.1 mA at 100 V 7.5 mA at 240 V
Current state 0 guaranteed	Logic input: 0...40 V and \leq 15 mA for 25 ms
Current state 1 guaranteed	Logic input: 79...264 V and \geq 2 mA for 25 ms
maximum output switching frequency	2 Hz
Load current	5 A at 250 V AC for logic output 5 A at 30 V DC for logic output
Permissible power	480 VA (AC-15), $I_e = 2$ A, 500000 cycles (output) 30 W (DC-13), $I_e = 1.25$ A, 500000 cycles (output)
maximum operating rate	1800 cyc/h
Contacts type and composition	1 NO + 1 NC fault signal 3 NO
Metering type	Earth-fault current Phase current I1, I2, I3 RMS Imbalance current Temperature Average current Iavg
Measurement accuracy	5...15 % earth fault current internal measurement 1 % voltage (100...830 V) 3 % power factor 5 % earth fault current external measurement +/- 30 min/year internal clock 0,02 temperature 5 % active and reactive power 0,02 current
Overvoltage category	III
Connection pitch	5.08 mm
Connections - terminals	Control circuit: connector 1 cable(s) 0.25...2.5 mm ² (AWG 24...AWG 14) flexible with cable end Control circuit: connector 1 cable(s) 0.2...2.5 mm ² (AWG 24...AWG 14) flexible without cable end Control circuit: connector 1 cable(s) 0.25...2.5 mm ² (AWG 24...AWG 14) flexible without cable end Control circuit: connector 1 cable(s) 0.2...2.5 mm ² (AWG 24...AWG 14) solid without cable end Control circuit: connector 2 cable(s) 0.2...1 mm ² (AWG 24...AWG 14) flexible with cable end Control circuit: connector 2 cable(s) 0.2...1.5 mm ² (AWG 24...AWG 14) flexible without cable end Control circuit: connector 2 cable(s) 0.5...1.5 mm ² (AWG 24...AWG 14) flexible without cable end Control circuit: connector 2 cable(s) 0.2...1 mm ² (AWG 24...AWG 14) solid without cable end
Tightening torque	Control circuit: 0.5...0.6 N.m flat screwdriver 3 mm
Pollution degree	3

Electromagnetic compatibility	<p>Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2</p> <p>Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3</p> <p>Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4</p> <p>Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming to EN/IEC 61000-4-4</p> <p>Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC 61000-4-11</p> <p>Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6</p> <p>Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5</p> <p>Temperature sensor: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5</p> <p>Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5</p> <p>Communication: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5</p> <p>Relay outputs and supply: surges (serial mode), 2 kV, conforming to EN/IEC 61000-4-5</p> <p>Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC 61000-4-5</p> <p>Control circuit: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5</p>
Width	91 mm
Height	61 mm
Depth	122.5 mm
Net weight	0.53 kg
Web services	Web server
Compatibility code	LTMR

Environment

Standards	<p>IEC 60947-4-1</p> <p>CSA C22.2 No 14</p> <p>IACS E10</p> <p>EN 60947-4-1</p> <p>UL 508</p>
Product certifications	<p>LROS (Lloyds register of shipping)</p> <p>DNV</p> <p>UL</p> <p>EAC</p> <p>GL</p> <p>CCC</p> <p>BV</p> <p>ABS</p> <p>KERI</p> <p>ATEX</p> <p>NOM</p> <p>RINA</p> <p>RMRoS</p> <p>C-Tick</p> <p>CSA</p>
Protective treatment	<p>12 x 24 hour cycles conforming to EN/IEC 60068-2-30</p> <p>48 h conforming to EN/IEC 60070-2-11</p> <p>TH conforming to EN/IEC 60068</p>
Fire resistance	<p>650 °C conforming to EN/IEC 60695-2-12</p> <p>960 °C conforming to UL 94</p>
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C
Operating altitude	<= 2000 m without derating
Mechanical robustness	<p>Vibrations mounted on symmetrical rail: 1 Gn, 5...300 Hz conforming to EN/IEC 60068-2-6</p> <p>Vibrations plate mounted: 4 Gn, 5...300 Hz conforming to EN/IEC 60068-2-6</p> <p>Shocks half sine wave acceleration: 15 Gn for 11 ms conforming to EN/IEC 60068-2-27</p>
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	10.0 cm
Package 1 Length	13.5 cm
Package 1 Weight	534.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.685 kg

Logistical informations

Country of origin	CN
--------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	Fc01c523-9a07-4dfa-988f-c721d4816782
Halogen-free status	Halogen free plastic parts product
PVC free	Yes

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins