


Product datasheet

Specifications



auxiliary contact - 4 OC

Local distributor code:

387348265

48198

EAN Code: 3303430481980

Main

Product or component type	Auxiliary contact
Device short name	4 OF
Range compatibility	Masterpact MasterPact NW
Signal contacts composition	4 NO/NC

Complementary

Auxiliary contacts type	Standard Low level
Mounting mode	Fixed
Breaking capacity (A)	AC-12: 10 A at 240/380 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 10 A at 480 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 6 A at 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 DC-12: 10 A at 24/48 V DC 50/60 Hz conforming to EN/IEC 60947-2 DC-12: 10 A at 125 V DC 50/60 Hz conforming to EN/IEC 60947-2 DC-12: 3 A at 250 V DC conforming to EN/IEC 60947-2 DC-12: 8 A at 480 V AC 50/60 Hz conforming to UL 489 DC-12: 6 A at 600 V AC 50/60 Hz conforming to UL 489 6 A at 250 V DC 50/60 Hz conforming to UL 489
Minimum load	100 mA at 24 V 2 mA at 15 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	7.0 cm
Package 1 Length	4.0 cm
Package 1 Weight	1.042 kg

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No