



PRODUCT-DETAILS

XT3S 225 TMF 175-1750 3p F F UL/CSA

XT3S 225 TMF 175-1750 3p F F UL/CSA



General Information	
Extended Product Type:	XT3S 225 TMF 175-1750 3p F F UL/CSA
Product ID:	1SDA075136R1
EAN:	8015644791131
Catalog Description:	XT3S 225 TMF 175-1750 3p F F UL/CSA
Long Description:	C.BREAKER TMAX XT3S 225 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 175-1750 A
Display Name:	XT3S 225 TMF 175-1750 3p F F UL/CSA

ABB EcoSolutions	
ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions:	9AKK108468A2350
Environmental Product Declaration - EPD:	9AKK108468A2294
Extended Product Lifetime:	Product Modularity
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 56.6 %

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
Toxic Substances Control Act - TSCA:	9AKK108467A8326

Environmental

Environmental Information:	9AKK108467A6707
-----------------------------------	-----------------

Ordering

Order Code US and Canada:	XT3SU3175AFF000XXX
EAN:	8015644791131
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	105 mm
Product Net Height:	150 mm
Product Net Depth / Length:	70 mm
Product Net Weight:	1.7 kg

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	155 mm
Package Level 1 Height:	190 mm
Package Level 1 Depth / Length:	155 mm
Package Level 1 Gross Weight:	1.7 kg
Package Level 1 EAN:	8015644791131

Additional Information

Circuit Breaker Type to be Associated:	Power Distribution
Product Main Type:	SACE Tmax XT

Product Name:	Moulded Case Circuit Breaker
Product Type:	Automatic Circuit Breaker
Suitable for Product Class:	SACE Tmax XT
Version:	F
CAD Dimensional Drawing:	1SDH001295R0409

Technical

Connecting Capacity Main Circuit:	Busbar 85..192 mm ²
Current Type:	AC/DC
Electrical Durability:	120 cycles per hour 8000 cycle
Mechanical Durability:	240 cycles per hour 25000 cycle
Number of Poles:	3P
Opening Time:	CB with SOR 30 ms CB with UVR 30 ms
Order Multiple:	1 piece
Power Loss:	at Rated Operating Conditions per Pole 10.1 W
Rated Current (I_n):	175 A
Rated Instantaneous Short-Circuit Current Setting (I_i):	1750 A
Rated Operational Voltage:	600Y/347 V AC 500 V DC
Rated Uninterrupted Current (I_u):	225 A
Rated Voltage (U_r):	600Y/347 V
Recommended Screw Driver:	Main Circuit M8
Release:	TMF
Release Type:	TM
Setting Range:	175 A
Short-Circuit Performance Level:	S
Standards:	UL489
Sub-type:	XT3
Terminal Connection Type:	Front
Terminal Type:	Bolt
Tightening Torque:	8 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489:	(240 V AC) 65 kA (480 V AC) 35 kA (600Y / 347 V AC) 10 kA (250 V DC) 2 Poles in Series 35 kA (500 V DC) 3 Poles in Series 35 kA
---	---

Certificates and Declarations

ATEX Certificate:	No certification needed
CSA Certificate (Intrinsic Safe):	9AKK10103A3907
Data Sheet, Technical Information:	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE:	9AKK106713A5530
UL Certificate:	1SDL000163R0113
VDE Certificate:	No certification needed
Dimension Diagram:	1SDH000720R0100
Mechanical Drawings:	1SDH000720R0100
Wiring Diagram:	1SDM000068R0001
Instructions and Manuals:	1SDH000720R0003

External Classifications and Standards

ETIM 9:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC):	4927 >> Molded case circuit breakers
Object Classification Code:	Q
UNSPSC:	39121616
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
eClass:	V11.1 : 27370409

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Moulded Case Circuit Breakers > Tmax XT

