



PRODUCT-DETAILS

E4S/MS40004pWMPnew

E4S/MS 4000 4p W MP new



General Information

Extended Product Type:	E4S/MS40004pWMPnew
Product ID:	1SDA059004R1
EAN:	8015644613631
Catalog Description:	E4S/MS 4000 4p W MP new
Long Description:	SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E4S/MS 4000A FOUR-POLE NEW
Display Name:	E4S/MS40004pWMPnew

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	Document availability on demand

Environmental

Environmental Information:	9AKK10103A6076
----------------------------	----------------

Ordering

EAN:	8015644613631
------	---------------

Minimum Order Quantity:	1 piece
-------------------------	---------

Customs Tariff Number:	85362090
------------------------	----------

Dimensions

Product Net Width:	684 mm
--------------------	--------

Product Net Height:	461 mm
---------------------	--------

Product Net Depth / Length:	396.5 mm
-----------------------------	----------

Product Net Weight:	96 kg
---------------------	-------

Container Information

Package Level 1 Units:	1 piece
------------------------	---------

Package Level 1 Width:	515 mm
------------------------	--------

Package Level 1 Height:	600 mm
-------------------------	--------

Package Level 1 Depth / Length:	920 mm
---------------------------------	--------

Package Level 1 Gross Weight:	116 kg
-------------------------------	--------

Package Level 1 EAN:	8015644609139
----------------------	---------------

Additional Information

Product Main Type:	SACE Emax
--------------------	-----------

Product Name:	Switch Disconnecter
---------------	---------------------

Product Type:	Air Circuit Breaker
---------------	---------------------

Version:	W
----------	---

Technical

Current Type:	AC
---------------	----

Electrical Durability:	5000 cycle 10 cycles per hour
------------------------	----------------------------------

Mechanical Durability:	15000 cycle 60 cycles per hour
------------------------	-----------------------------------

Number of Poles:	4P
------------------	----

Power Loss:	660 W
-------------	-------

Rated Current (I _n):	4000 A
----------------------------------	--------

Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current (I_e):	4000 A
Rated Operational Voltage:	690 V AC 250 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 75 kA for 3 s 75 kA
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Short-Circuit Performance Level:	S
Standards:	IEC
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers

Certificates and Declarations

Data Sheet, Technical Information:	1SDC200006D0209
Declaration of Conformity - CE:	1SDL000165R0016
Instructions and Manuals:	1SDH000460R0002

External Classifications and Standards

Object Classification Code:	Q
WEEE Category:	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Air Circuit Breakers > Emax

