



Withdrawable circuit breaker without guide frame, IEC 60947-2, frame size 3, 3-poles, $I_n=4000\text{A}$ up to 690V AC 50/60Hz, breaking capacity H $I_{cu}=100/85\text{kA}$ at 500/690V, Trip unit ETU600 LSI upgrade ready, color display, bluetooth and USB interface, Protection LT, ST, INST, N-protection required an external N-sensor, incl. trip alarm switch (1xCO), without Com & metering function with manual and motorized operating mechanism (M) 208-240 V AC / 220-250 V DC, Storage status and ready-to-close signaling switches, Auxiliary switches 4NO+4NC, Closing coil (CC) 100% OP 208-240 V AC / 220-250 V DC, applicable for continuous duty, without Remote trip alarm reset coil (RR), without 2nd shunt trip, Shunt trip (ST) 100% OP 208-240 V AC / 220-250 V DC, suitable for continuous duty, Option S07 = Locking provision against unauthorized closing Secured Open; for padlock device Padlocks are not included. Option S33 = Locking provision for Padlock device for charging handle padlocks are not included Option T40 = Door sealing frame IP41

Model	
product brand name	SENTRON
product designation	Air circuit breaker
suitability for use	circuit breaker
size of the circuit-breaker	III
number of poles	3
position / of neutral conductor	no internal N-conductor
fastening method	withdrawable circuit breaker without guide frame
design of the product	AC application
type of the driving mechanism	manual operating mechanism/spring charging motor with spring charge signaling switch
design of the electronic trip unit	ETU600 LSI
Weight	101.863 kg
Net Weight	84.863 kg
General technical data	
insulation voltage / rated value	1000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
Current	
continuous current / rated value / maximum	4000 A
continuous current / rated value	4000 A
Switching capacity and short-time withstand current, according to IEC 60947-2	
switching capacity class of the circuit breaker	H
maximum short-circuit current breaking capacity (I_{cu})	
• at 500 V / rated value	100 kA
• at 690 V / rated value	85 kA
operating short-circuit current breaking capacity (I_{cs})	
• at 500 V / rated value	100 kA
• at 690 V / rated value	85 kA
short-circuit current making capacity (I_{cm})	
• at 500 V / rated value	220 kA
• at 690 V / rated value	187 kA
short-time withstand current (I_{cw}) / at 500 V AC	
• for 0.5 s / rated value	100 kA
• for 1 s / rated value	100 kA
• for 2 s / rated value	100 kA
• for 3 s / rated value	100 kA

short-time withstand current (I _{cw}) / at 690 V AC	
<ul style="list-style-type: none"> • for 0.5 s / rated value • for 1 s / rated value • for 2 s / rated value • for 3 s / rated value 	85 kA 85 kA 85 kA 85 kA
Electronic release unit	
product feature	
<ul style="list-style-type: none"> • upgradable • Bluetooth and USB interface • decoder for basic protection functions • display and function keys • SENTRON powerconfig configuration software 	Yes Yes Yes Yes Yes
Basic protection functions	
product feature / for L-tripping	
<ul style="list-style-type: none"> • can be switched on/off • selectable characteristic function • decoder and infinite adjustability are selectable with eSet 	Yes Yes Yes
set values setting current (I _r) / for L-tripping / with I _{2t} characteristic	0.5; 0.6; 0.7; 0.75; 0.8; 0.85; 0.9; 0.95; 1
reference value setting current (I _r) / for L-tripping / with I _{2t} characteristic	x I _n
set values delay time (t _r) / for L-tripping / with I _{2t} characteristic	1;2;5;8;10;14;17;21;25
reference value delay time (t _r) / for L-tripping / with I _{2t} characteristic	s
set values setting current (I _r) / for L-tripping / with I _{2t} characteristic / for eSet	0.4-1;0.001
adjustable absolute value setting current (I _r) / for L-tripping / with I _{2t} characteristic / for eSet	
<ul style="list-style-type: none"> • minimum • maximum 	1600 A 4000 A
set values delay time (t _r) / for L-tripping / with I _{2t} characteristic / for eSet	0.5-30;0.001
set values setting current (I _r) / for L-tripping / with I _{4t} characteristic / for eSet	0.4-1;0.001
set values delay time (t _r) / for L-tripping / with I _{4t} characteristic / for eSet	0.5-5;0.001
adjustable absolute value setting current (I _r) / for L-tripping / with I _{4t} characteristic / for eSet	
<ul style="list-style-type: none"> • minimum • maximum 	1600 A 4000 A
L: Overload protection N-conductor	
product feature / with neutral conductor protection / can be switched on/off	Yes
setting values setting current (I _{nN}) / for N-tripping	0.2-2;0.001
reference value setting current (I _{nN}) / for N-tripping	x I _n
adjustable setting current (I _{nN}) / for N-tripping	
<ul style="list-style-type: none"> • minimum • maximum 	800 A 8000 A
S: delayed short-circuit protection ST	
product feature / for S-tripping	
<ul style="list-style-type: none"> • independent of direction / can be switched on/off • independent of direction / selectable characteristic function • decoder and infinite adjustability are selectable with eSet 	Yes Yes Yes
S: delayed short-circuit protection ST, settings values I_{0t}	
set values setting current (I _{sd}) / for S-tripping / with I _{0t} characteristic	1.5;2;2.5;3;4;5;6;8;10
reference value setting current (I _{sd}) / for S-tripping / with I _{0t} characteristic	x I _r
set values delay time (t _{sd}) / for S-tripping / with I _{0t} characteristic	0.08;0.15;0.22;0.3;0.4
reference value delay time (t _{sd}) / for S-tripping / with I _{0t} characteristic	s
set values setting current (I _{sd}) / for S-tripping / with I _{0t}	0.6-10;0.001

characteristic / for eSet / independent of direction	
adjustable absolute value setting current (I _{sd})	
<ul style="list-style-type: none"> • for S-tripping / with I0t characteristic / for eSet / independent of direction / minimum 	2400 A
<ul style="list-style-type: none"> • at 500 V / for S-tripping / with I0t characteristic / for eSet / independent of direction / maximum 	80 kA
<ul style="list-style-type: none"> • at 690 V / for S-tripping / with I0t characteristic / for eSet / independent of direction / maximum 	68 kA
set values delay time (tsd) / for S-tripping / with I0t characteristic / for eSet / independent of direction	0.02-0.4;0.001
S: delayed short-circuit protection ST, settings values I2t	
set values setting current (I _{sd}) / for S-tripping / with I2t characteristic	1.5;2;2.5;3;4;5;6;8;10
reference value setting current (I _{sd}) / for S-tripping / with I2t characteristic	x I _r
set values delay time (tsd) / for S-tripping / with I2t characteristic	0.1;0.2;0.3;0.4
set values setting current (I _{sd}) / for S-tripping / with I2t characteristic / for eSet / independent of direction	0.6-10;0.001
adjustable absolute value setting current (I _{sd})	
<ul style="list-style-type: none"> • for S-tripping / with I2t characteristic / for eSet / independent of direction / minimum 	2400 A
<ul style="list-style-type: none"> • at 500 V / for S-tripping / with I2t characteristic / for eSet / independent of direction / maximum 	80 kA
<ul style="list-style-type: none"> • at 690 V / for S-tripping / with I2t characteristic / for eSet / independent of direction / maximum 	68 kA
set values delay time (tsd) / for S-tripping / with I2t characteristic / for eSet / independent of direction	0.02-0.4; 0.001
product feature / for I-tripping	
<ul style="list-style-type: none"> • can be switched on/off 	Yes
<ul style="list-style-type: none"> • decoder and infinite adjustability are selectable (with eSet) 	Yes
set values setting current (I _i) / for I-tripping	1.5;2;3;4;6;8;10;12;15
reference value setting current (I _i) / for I-tripping	x I _{ln}
tripping factor setting current (I _{imax}) / for I-tripping	0.8
reference value setting current (I _{imax}) / for I-tripping	x I _{cs}
set values setting current (I _i) / for I-tripping / for eSet	1.5-15;0.001
adjustable absolute value setting current (I _i)	
<ul style="list-style-type: none"> • for I-tripping / for eSet / minimum 	6000 A
<ul style="list-style-type: none"> • at 500 V / for I-tripping / for eSet / maximum 	80 kA
<ul style="list-style-type: none"> • at 690 V / for I-tripping / for eSet / maximum 	68 kA
G: ground fault GF	
product feature / for G-tripping	
<ul style="list-style-type: none"> • selectable characteristic function 	No
Further protective functions	
protection function	
<ul style="list-style-type: none"> • maintenance mode DAS+ 	Yes
Measuring functions	
measurement function	
<ul style="list-style-type: none"> • current measurement 	Yes
Communication	
communication function	No
Service Life	
mechanical service life (operating cycles)	
<ul style="list-style-type: none"> • without support / typical 	7500
<ul style="list-style-type: none"> • with support / typical 	15000
electrical endurance (operating cycles)	
<ul style="list-style-type: none"> • at 690 V / without support / typical 	2000
<ul style="list-style-type: none"> • at 690 V / with support / typical 	15000
Dimensions	
height	468 mm
width	704 mm
depth	471 mm

Auxiliary circuit	
design of the auxiliary switch	4 NO + 4 NC
number of NC contacts / for auxiliary contacts	4
number of NO contacts / for auxiliary contacts	4
number of CO contacts / for auxiliary contacts	0

Internal accessories	
product component	
• undervoltage release	No
• voltage trigger	Yes
• trip indicator	Yes
• motor drive	Yes

Environmental conditions	
protection class IP / on the front	IP41
ambient temperature / during operation	
• minimum	-40 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C

Certificates	
reference code / according to IEC 81346-2	Q

Approvals / Certificates

Environment	General Product Approval
-------------	--------------------------



[Confirmation](#)



General Product Approval	EMV	Radio Equipment Type Approval Certificate
--------------------------	-----	---



[Miscellaneous](#)

[Industry Canada \(IC\)](#)

Radio Equipment Type Approval Certificate	Test Certificates	Maritime application
---	-------------------	----------------------

[Miscellaneous](#)

[FCC](#)

[Special Test Certificate](#)

[Miscellaneous](#)



Maritime application	other
----------------------	-------



[Manufacturer Declaration](#)

[Confirmation](#)



Dangerous goods

[Dangerous goods information](#) [Transport Information](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA1340-5AE30-8EA4-Z_S07+S33+T40

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3WA1340-5AE30-8EA4-Z_S07+S33+T40

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA1340-5AE30-8EA4-Z_S07+S33+T40

CAX-Online-Generator

<https://www.siemens.com/cax>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



