



## E3S-CL2-M1J 0.3M

Photoelectric sensor distance setting BGS, 5-500mm, NPN/PNP, M12 pigtail

# Specifications

<b>Shape</b>	Cuboid
<b>Sensing method</b>	Background suppression
<b>Sensing distance</b>	500 mm
<b>Sensing distance (min.)</b>	5 mm
<b>Setting method</b>	Manual adjustment
<b>Connection method</b>	M12 pigtail connector
<b>Cable length</b>	0.3 m
<b>Output type</b>	PNP/NPN
<b>Operation mode</b>	Dark-ON, Light-ON
<b>Response time</b>	2 ms
<b>Material housing</b>	Zinc
<b>Thread size</b>	Other
<b>Product Width (unpacked)</b>	15.4 mm
<b>Product Height (unpacked)</b>	43.7 mm
<b>Product Depth (unpacked)</b>	40 mm
<b>Type of light</b>	Infrared light
<b>Spot size</b>	60 mm
<b>Power supply voltage</b>	10-30 V
<b>Degree of protection (IP)</b>	IP67

## Related products



### M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

## Downloads

CAD Library



### E3S-CL Series Datasheet

EN PDF 1.2 MB