



MY2IN-D2-GS-R DC100/110

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 100/110 VDC

Specifications

Mounting method	With plug-in socket
Usage	General purpose
Poles	2
Rated carry current	10 A
Coil voltage	110 V
Operation voltage	DC
Contact material	Ag
Contact description	DPDT
Features	Diode, LED, Test button, Transparent case, With mechanical indicator
Terminal type	Plug-in, Solder

Fits to



PY08-02

Socket, back-connecting, 8-pin, PCB terminals



PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF08A-N

Socket, DIN rail/surface mounting, 8-pin, screw terminals (IEC/VDE)



PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)



Industrial Relays Brochure

EN PDF 2.77 MB



MY-GS- R/MY(s)/MYK/MYQ/MYH Miniature Power Relays Datasheet

EN PDF 20.3 MB



OMRON Manufacturing Know-How: High Quality Relays Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB