


Product datasheet

Specifications

FR.PL.3-4 NSX/CVS250 V.FIXED TOG/ROT 5M



LVS03243

EAN Code: 3606481872944

Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out
Installed device	<p>ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation</p> <p>EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle - vertical installation</p> <p>EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>EasyPact: fixed CVS250 without earth leakage protection - control: toggle - vertical installation</p> <p>EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX100...160 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: plug-in NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: drawout NSX100...160 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: drawout NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: drawout NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX250 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: plug-in NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: plug-in NSX250 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: drawout NSX250 without earth leakage protection - control: toggle - vertical installation</p> <p>ComPact: drawout NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: drawout NSX250 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation</p>

Poles description	4 x 3P: mounting plate support: CVS100...160 vertical installation 3 x 4P: mounting plate support: CVS100...160 vertical installation 4 x 3P: mounting plate support: CVS250 vertical installation 3 x 4P: mounting plate support: CVS250 vertical installation 4 x 3P: mounting plate support: NSX100...160 vertical installation 3 x 4P: mounting plate support: NSX100...160 vertical installation 4 x 3P: mounting plate support: NSX250 vertical installation 3 x 4P: mounting plate support: NSX250 vertical installation 2 x 3P: mounting plate support: NSX100...160 vertical installation 2 x 4P: mounting plate support: NSX100...160 vertical installation 2 x 3P: mounting plate support: NSX250 vertical installation 2 x 4P: mounting plate support: NSX250 vertical installation
--------------------------	--

Operating position	Vertical
---------------------------	----------

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
--------------------------------------	---

Connection position	Linergy FC Direct connection
----------------------------	---------------------------------

Number of vertical modules [50 mm]	5
---	---

Standards	IEC 61439-2 IEC 61439-1
------------------	----------------------------

Product certifications	ASTA
-------------------------------	------

Material	Steel
-----------------	-------

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
-----------------------------	--

Surface finish	Matt Textured
-----------------------	------------------

Colour	White (RAL 9003)
---------------	------------------

Width	500 mm
--------------	--------

Height	250 mm
---------------	--------

Net weight	0.82 kg
-------------------	---------

Quantity per set	Set of 1
-------------------------	----------

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 3P 4 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 4P 3 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 3P 4 Linergy FC 8

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 3P 4 Linergy FC 8

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 4P 3 Linergy FC 8

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 4P 3 Linergy FC 8

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 3P 4 direct 10

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 4P 3 direct 10

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 3P 4 direct 10

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in direct front rotary handle vertical 4P 3 direct 10

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 3P 4 direct 10

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in motor mechanism vertical 4P 3 direct 10

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout toggle vertical 3P 2 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout toggle vertical 4P 2 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout direct front rotary handle vertical 3P 2 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout direct front rotary handle vertical 4P 2 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout motor mechanism vertical 3P 2 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without drawout motor mechanism vertical 4P 2 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 Linergy FC 7

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 Linergy FC 7

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 Linergy FC 7

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 Linergy FC 7

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 direct 9

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 3P 4 Linergy FC 8

650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without plug-in toggle vertical 4P 3 Linergy FC 8

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed toggle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed toggle vertical 3P 4 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed toggle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed toggle vertical 4P 3 direct with long terminal shield 11

600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G floor-standing enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11
600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed toggle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed toggle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 9
600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed toggle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed toggle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed toggle vertical 4P 3 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed toggle vertical 4P 3 direct with long terminal shield 11
600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct with long terminal shield 11
600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11
600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct with long terminal shield 11

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	26.000 cm
Package 1 Length	51.000 cm
Package 1 Weight	824.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	16.500 cm
Package 2 Width	27.400 cm
Package 2 Length	52.700 cm
Package 2 Weight	8.537 kg
Unit Type of Package 3	P12
Number of Units in Package 3	270
Package 3 Height	94.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	236.480 kg

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

Nej

Technical Illustration

Assembly's dimensions

