



 PRODUCT-DETAILS

E3S-A 2500 PR121/P-LI In=2500A 3p F HR

E3S-A 2500 PR121/P-LI In=2500A 3p F HR



General Information

Extended Product Type:	E3S-A 2500 PR121/P-LI In=2500A 3p F HR
Product ID:	1SDA057527R1
EAN:	8015644597900
Catalog Description:	E3S-A 2500 PR121/P-LI In=2500A 3p F HR
Long Description:	SACE EMAX CIRCUIT-BREAKER E3S-A 2500A UL THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED
Display Name:	E3S-A 2500 PR121/P-LI In=2500A 3p F HR

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	Document availability on demand
SCIP:	ee767f02-7180-4847-9c5f-02fdf30fc3a2 Italy

Simplified SCIP:	09777dba-e8d2-4320-9765-fce888d3de94 Bulgaria 7e1e8f83-a893-4872-9e86-98ccececd153 Germany 6f0acc03-f840-4238-a5cd-2c52c7aaf8ac Germany a724f7bf-1c8f-4d00-9f31-bd260e600d49 Denmark bec62c59-8d11-4680-9b71-88f4ff6efb23 Poland 21b48313-98ea-4aa4-b9bb-8d1e808352a8 Finland e3a586db-dfeb-4695-a42b-2e1c3c065874 Poland d7ce6eec-86e4-4ef3-875e-67135f1846e1 Netherlands 59db5e85-3105-4d16-839b-19103d167d1a Norway 785fd53d-5b34-476d-9ca9-8c6a3a997e59 Belgium 4e9eecf0-b888-4902-a6a8-5382add5d57f Croatia 257c6601-4185-4ec3-9bf0-12d296f828fe Germany 3dc03628-fb87-49dd-9ddd-4240d627bd9b Czech Republic ce654001-e51a-4bc4-90d7-682854b1cb9d France 30e66eb4-5577-429d-bd68-5326c03d1f31 France 8d843524-97c0-4821-822c-7c255fc6d63f Sweden 688bb16d-7ca3-4bca-aba6-a8645bf013d4 Hungary db13c0e4-e476-49e7-b098-70fc7eb572ce Belgium c46b8f12-b8fe-4487-a7de-77e512499405 Greece b03a85bf-5ab5-4f63-a395-2680f4d64b28 Germany 89113f87-263c-4be5-9f2f-98b33d10d81f Germany 2495d2d2-b9f8-4b21-b280-5fa57515c9d3 Estonia 8feca682-4a03-4d30-a3ab-228ab5fb37c3 Sweden 96c2f5cb-d85b-4fd6-834a-436d0a2dfe21 Hungary 33d4b8f0-435d-4685-a490-ef2004e0e629 Spain 131f0096-3ec3-46e1-9d7f-c1280127aa27 Portugal a0dad4e4-7108-41ce-9bfd-2dcde7a1226f Poland
-------------------------	--

Environmental

Environmental Information:	9AKK10103A6076
-----------------------------------	----------------

Ordering

EAN:	8015644597900
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	404 mm
Product Net Height:	418 mm
Product Net Depth / Length:	302 mm
Product Net Weight:	60 kg

Container Information

Package Level 1 EAN:	8015644597900
-----------------------------	---------------

Additional Information

Product Main Type:	SACE Emax
---------------------------	-----------

Product Name:	Air Circuit Breaker
Product Type:	CB
Version:	F

Technical

Current Type:	AC
Electrical Durability:	An error has occurred while processing HtmlTextBox ": Name cannot begin with the ' ' character, hexadecimal value 0x20. Line 1, position 12.
Mechanical Durability:	15000 cycle 30 cycles per hour
Number of Poles:	3P
Power Loss:	at Rated Operating Conditions per Pole 205 W
Rated Current (I_n):	2500 A
Rated Operational Current (I_e):	2500 A
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(240 V AC) 85 kA (480 V AC) 85 kA (600 V AC) 65 kA
Rated Uninterrupted Current (I_u):	2500 A
Rated Voltage (U_r):	600 V
Release:	PR121/P-LI
Release Type:	EL
Short-Circuit Performance Level:	S
Standards:	UL 1066
Sub-type:	E3
Terminal Connection Type:	Fixed Circuit-Breakers Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(240 V AC) 85 kA (480 V AC) 65 kA (600 V AC) 65 kA
--	--

Certificates and Declarations

Data Sheet, Technical Information:	1SDC200008D0202
Declaration of Conformity - CE:	1SDL000165R0015
Instructions and Manuals:	1SDH000532R0002

External Classifications and Standards

WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
-----------------------	--

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Air Circuit Breakers > Emax

