



032U5701 [🔗](#)

Solenoid valve, EV210B, Function: NC, G, 1/8, 0.08 m³/h, EPDM

Media recommendations: Water & Brine, Approval: DNVGL-CG-0339; GL; PZH,

Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

PRODUCT DETAILS

Gross weight	0.19 Kilogram
Net weight	0.167 Kilogram
Volume	0.253 Liter
EAN	5702423012961
Type	EV210B
Product group	Solenoid valves
Product Name Description	Solenoid valve
Actuator	B
Actuator size	13.5 mm
Actuator size [in]	0.53 in
Actuator system [mm]	13.5 mm
Ambient temperature max. [°C]	80 °C
Ambient temperature max. [°F]	176 °F
Application	Closed and Drain
Approval	DNVGL-CG-0339 GL PZH
Body material	Brass
China RoHS compliance	Yes with exemptions
China RoHS exemption clause	7.3
Connection Internal/External	Internal
Connection material	Brass
Connection size [in]	1/8
Connection standard	ISO 228-1
Connection type	G
Contains batteries	No
Cv value [gal/min]	0.09 gal/min
Differential pressure [bar] [max]	30 bar
Differential pressure [bar] [min]	0 bar
Differential pressure [psi] [max]	435 psi
Differential pressure [psi] [min]	0 psi
EEE category	5 small equipment (any external dimension < 50 cm)
Est. time to close, water [ms]	20 ms
Est. time to open, water [ms]	10 ms
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flow direction	Single-flow
Flow direction indicator	Embossed 1-way arrow

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Fluid Group	1
Function	NC
In scope of WEEE	Yes
Kv value [m³/h]	0.08 m ³ /h
Max media viscosity [cSt]	50 cSt
Max. test pressure [bar]	45 bar
Max. test pressure [psig]	653 psig
Max. Working Pressure [bar]	30 bar
Max. Working Pressure [psig]	435 psig
Media recommendations	Water & Brine
Media tolerance comments	140 °C/3.6 bar low press steam Neutral media
Medium temperature range [°C] [max]	120 °C
Medium temperature range [°C] [min]	-30 °C
Medium temperature range [°F] [max]	248 °F
Medium temperature range [°F] [min]	-22 °F
Number of ways	2/2
Operation	Direct-operated
Orifice size [mm]	1.5 mm
Orifice size fraction [in]	1/16 in
Packing format	Multi pack
Parts Program name	EV210B
Product accessories	Solenoid valve accessories
Quantity per packing format	20 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
SCIP dossier no.	f39c9b5f-71a1-49e3- bc6d-20baa8f46870
SCIP dossier product name	EV210B brass NC - solenoid valve
Seal Material	EPDM
Serviceable	Solenoid valve spare parts
Specification key	EV210B 1.5B G 18E NC000
Type designation	EV210B 1.5

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

018F7351 [↗](#)
Solenoid coil, BB230AS, DIN Spade, Supply voltage [V] AC: 230, Multi pack

Electrical connection: DIN Spade, Supply voltage [V] AC: 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**018F7358** [🔗](#)**Solenoid coil, BB024AS, DIN Spade, Supply voltage [V] AC: 24, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

**018F7397** [🔗](#)**Solenoid coil, BB024DS, DIN Spade, Supply voltage [V] DC: 24, Multi pack**

Solenoid coil, Product Type: BB024DS, Supply voltage [V] DC: 24, Enclosure rating IP: IP00, Coil connection: DIN Spade, Actuator size: 13.5 mm

**018F7396** [🔗](#)**Solenoid coil, BB012DS, DIN Spade, Supply voltage [V] DC: 12, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] DC: 12, Enclosure rating IP: IP00

**018F6701** [🔗](#)**Solenoid coil, BE230AS, Terminal box, Supply voltage [V] AC: 220 - 230, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 220 - 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67

**018F6707** [🔗](#)**Solenoid coil, BE024AS, Terminal box, Supply voltage [V] AC: 24, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67

**018F6783** [🔗](#)**Solenoid coil, BE240CS, Terminal box, Supply voltage [V] AC: 208 - 240, Multi pack**

Electrical connection: Terminal box, Supply voltage [V] AC: 208 - 240, Frequency [Hz]: 50/60 Hz, Enclosure rating IP: IP67

**042N7501** [🔗](#)**Solenoid coil, BA230A, DIN Spade, Supply voltage [V] AC: 220 - 230, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] AC: 220 - 230, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

**042N7508** [🔗](#)**Solenoid coil, BA024A, DIN Spade, Supply voltage [V] AC: 24, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] AC: 24, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00

**042N7551** [🔗](#)**Solenoid coil, BA024D, DIN Spade, Supply voltage [V] DC: 24, Multi pack**

Electrical connection: DIN Spade, Supply voltage [V] DC: 24, Enclosure rating IP: IP00

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.