



E3Z-LS81 0.5M

Photoelectric sensor, rectangular housing, red LED, background suppression, 200 mm, PNP, Light-ON/Dark-ON, 0.5 m cable

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	200 mm
Sensing distance (min.)	20 mm
Setting method	Manual adjustment
Connection method	Cable
Cable length	0.5 m
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	PBT
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	20 mm
Type of light	Polarity free red light
Power supply voltage	12-24 V
Degree of protection (IP)	IP67



E39-L104

Mounting bracket for E3Z sensor, standard, vertical mounting



E39-L142

Mounting Bracket, protective side wall (for E3Z)



E39-L144

Sensor mounting Bracket, Protective bracket for E3Z pre-wired



E39-L150

Sensor mounting Bracket for E3Z, 100mm high post



E39-L151

Sensor mounting Bracket, for E3Z, 200mm high post



E39-L153

Mounting bracket for E3Z sensor, L shape, for prewired



E39-L43

Mounting bracket for E3Z sensor, side mounting



E39-L44


Mounting bracket for E3Z sensor, rear mounting



E39-L98

Protective metal cover for E3S-A/E3Z vertical sensor

CAD Library



E3Z **Brochure**

EN PDF 1.34 MB



E3Z Compact **Photoelectric Sensor** **with Built-in Amplifier** **Datasheet**

EN PDF 3.16 MB



IO-Link Series **Brochure**

EN PDF 6.41 MB



Sysmac: A Fully **Integrated Platform** **Brochure**

EN PDF 19.1 MB