

# Product datasheet

Specifications



## PratiKa wander plug - straight - 16 A - 2P + E - 200...250 V AC - IP67

PKX16M723

EAN Code: 3303432009540

! Discontinued

### Main

Range	Mureva
Product or component type	Wander plug
Device short name	Mureva plug
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

### Complementary

Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Fast connection
Cable cross section	1...2.5 mm <sup>2</sup>
Cable outer diameter	8...15 mm
cable entry	Fair lead Cable gland
Thread type	Pg 16
Net weight	0.167 kg
Height	129 mm
Width	73 mm
Depth	73 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue

### Environment

Standards	IEC 60309-2 IEC 60309-1
-----------	----------------------------

<b>IP degree of protection</b>	IP67 conforming to IEC 60529
<b>IK degree of protection</b>	IK08 conforming to EN 62262
<b>Fire resistance</b>	850 °C conforming to IEC 60695-2-11
<b>Relative humidity</b>	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
<b>Operating altitude</b>	2000 m
<b>Ambient air temperature for operation</b>	35 °C ( 86400 s ) -25...40 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7.500 cm
<b>Package 1 Width</b>	7.200 cm
<b>Package 1 Length</b>	13.500 cm
<b>Package 1 Weight</b>	153.900 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	12.400 cm
<b>Package 2 Width</b>	26.600 cm
<b>Package 2 Length</b>	27.000 cm
<b>Package 2 Weight</b>	1.660 kg
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	30
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	30.000 cm
<b>Package 3 Length</b>	40.000 cm
<b>Package 3 Weight</b>	5.020 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.5 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	661ec80b-b956-4b0a-92bb-53046f4cfb4c

## Use Longer




### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	33
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Exploded view

---



Technical Illustration

Exploded view

---



Technical Illustration

Exploded view

---

