

# Product datasheet

Specifications



## Stainless 304L PC rack, Micro-beaded finishing, H1600xW600xD600mm.

Local distributor code:  
398322908

NSYSMX16660PC

⚠ Discontinued on: 7 Aug 2023

⚠ Discontinued

EAN Code: 3606480155727

## Main

|                      |   |
|----------------------|---|
| Range                | PanelSeT  |
| Product name         | PanelSeT SMX  |
| enclosure type       | Computer protection<br>PC application   |
| category             | Compact enclosure   |
| nominal height       | 1600 mm   |
| nominal width        | 600 mm  |
| nominal depth        | 600 mm  |
| product installation | Floor-standing  |
| Device composition   | 1 body<br>1 cable gland plate<br>1 partial door for keyboard<br>1 partial door for PC screen<br>1 partial door for printer support/CPU<br>1 rear door |

## Complementary

|                             |   |
|-----------------------------|---|
| Body type                   | Single piece body folded and welded   |
| Door type                   | Glazed partial<br>Plain partial<br>Plain  |
| Door opening side           | Reversible (120 °)  |
| Number of doors             | Front: 2 door(s)<br>Front: 1 door(s)<br>Rear: 1 door(s)   |
| Lock type                   | 3 mm double-bar lock  |
| Type of gland plate         | Plain   |
| Accessibility for operation | Rear<br>Front   |
| Mounting plate description  | Without mounting plate  |
| Material                    | Body and door: stainless steel 304L<br>Hinge: stainless steel<br>Door: Securit glass<br>Lock: zamak                 |
| Removable parts             | Cable gland plate by clips<br>Door by hinges rear<br>Partial doors by hinges front<br>Transparent shutter by screws |

|                       |   |
|-----------------------|---|
| <b>Surface finish</b> | Body and door: micro beaded<br>Securit glass: silkscreened<br>Lock: chromium plated |
| <b>Net weight</b>     | 100 kg  |

## Environment

|                                     |   |
|-------------------------------------|---|
| <b>Standards</b>                    | IEC 62208   |
| <b>IP degree of protection</b>      | IP55 conforming to IEC 60529 (even with the keyboard drawer open)                       |
| <b>IK degree of protection</b>      | IK10 conforming to IEC 62262 (plain door)<br>IK08 conforming to IEC 62262 (glazed door) |
| <b>Environmental characteristic</b> | Specific hygiene<br>Corrosive   |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 80.0 cm  |
| <b>Package 1 Width</b>              | 80.0 cm  |
| <b>Package 1 Length</b>             | 180.0 cm |
| <b>Package 1 Weight</b>             | 104.0 kg |

## Contractual warranty

|                             |    |
|-----------------------------|----|
| <b>Warranty (in months)</b> | 18 |
|-----------------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

SCIP Number

52da316e-d4e1-4114-85c0-32a03b2934fd

EU RoHS Directive

[Compliant](#)

## Use Longer



### Lifetime extension

Repair

No