



 PRODUCT-DETAILS

E4H-A 3600 PR121/P-LSI In=3600A 3p W MP

E4H-A 3600 PR121/P-LSI In=3600A 3p W MP



General Information

Extended Product Type:	E4H-A 3600 PR121/P-LSI In=3600A 3p W MP
Product ID:	1SDA057917R1
EAN:	8015644601805
Catalog Description:	E4H-A 3600 PR121/P-LSI In=3600A 3p W MP
Long Description:	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4H-A 3600A UL THREE-POLE OVERCURRENT RELEASE PR121/P-LSI R3600 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED
Display Name:	E4H-A 3600 PR121/P-LSI In=3600A 3p W MP

Material Compliance

REACH Declaration:	9AKK108466A1425
RoHS Declaration:	9AKK108466A1424
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT):	Document availability on demand

Environmental

Environmental Information: 9AKK10103A6076

Ordering

EAN: 8015644601805

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85362090

Dimensions

Product Net Width: 594 mm

Product Net Height: 461 mm

Product Net Depth / Length: 396.5 mm

Product Net Weight: 85 kg

Container Information

Package Level 1 EAN: 8015644601805

Additional Information

Product Main Type: SACE Emax

Product Name: Air Circuit Breaker

Product Type: CBMP

Version: W

Technical

Current Type: AC

Electrical Durability: An error has occurred while processing HtmlTextBox "": Name cannot begin with the ' ' character, hexadecimal value 0x20. Line 1, position 12.

Mechanical Durability: 8000 cycle
30 cycles per hour

Number of Poles: 3P

Power Loss: at Rated Operating Conditions per Pole 535 W

Rated Current (I_n): 3600 A

Rated Operational Current (I_e): 3600 A

Rated Service Short-Circuit Breaking Capacity (I_{cs}): (240 V AC) 100 kA
(480 V AC) 85 kA
(600 V AC) 85 kA

Rated Uninterrupted Current (I_u): 3600 A

Rated Voltage (U_r):	600 V
Release:	PR121/P-LSI
Release Type:	EL
Short-Circuit Performance Level:	H
Standards:	UL 1066
Sub-type:	E4
Terminal Connection Type:	Withdrawable Circuit-Breakers

Technical UL/CSA

Interrupting Rating acc. to UL1066:	(240 V AC) 100 kA (480 V AC) 85 kA (600 V AC) 85 kA
--	---

Certificates and Declarations

Data Sheet, Technical Information:	1SDC200008D0202
Declaration of Conformity - CE:	1SDL000165R0016
Instructions and Manuals:	1SDH000532R0002

External Classifications and Standards

WEEE Category:	4. Large Equipment (Any External Dimension More Than 50 cm)
-----------------------	---

Categories

Products > Low Voltage Products and Systems > Circuit Breakers > Air Circuit Breakers > Emax

