



023Z458191 [🔗](#)

Hermetic filter drier, DML, 16 cu.in., Steel Cu-plated

Inlet connection type: Solder, ODF, Outlet connection type: Solder, ODF, Core Size code: 16 cu.in., Packing format: Multi pack, Quantity per packing format: 12

PRODUCT DETAILS

Gross weight	0.706 Kilogram
Net weight	0.668 Kilogram
Volume	1.311 Liter
EAN	5702428649957
Type	DML
Product group	Filter driers
Product Name Description	Hermetic filter drier
Acid capacity [g]	1.2 g
Acid capacity [oz]	0.042 oz
Activated alumina [%]	0 %
Approval	UL
Body material	Steel
Braket	No
Brand	ELIMINATOR
China RoHS compliance	Yes
China RoHS exemption clause	No
Connection material	Steel Cu-plated
Contains batteries	No
Core	Solid core
Core Size code	16 cu.in.
Core type	Solid core
Drying Cap[Drops of Water]24°C	R134a: 559 R290: -- R32: 470 R404A: 582 R407C: 543 R410A: 506 R507: 610
Drying Cap[Drops of Water]52°C	R134a: 512 R290: -- R32: 433 R404A: 551 R407C: 500 R410A: 450 R507: 548
EU RoHS compliance	Yes
EU RoHS exemption clause	No
Filter application	High Moisture Capacity
Flow capacity [kW]	R134a: 38.7

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

	R290: 46.6 R32: 58.9 R404A: 27.2 R407C: 39.6 R410A: 40.2 R507: 26.4
Flow capacity [TR]	R134a: 11.0 R290: 13.2 R32: 16.8 R404A: 7.7 R407C: 11.3 R410A: 11.4 R507: 7.5
Flow direction indicator	Label printed 1-way arrow
Fluid Group	2
Inlet 1 connection size [in]	5/8 in
Inlet connection type	Solder, ODF
LiqCap Cond (ARI 710-2009)[SI]	Delta p=0.07bar tliq= 30°C tvap=-15°C
LiqCapCond (ARI 710-2009)[IMP]	Delta p=1psi tliq= 86°F tvap=5°F
Lubricants compatibility	Oilfree applications
Max. Working Pressure [bar]	46 bar
Max. Working Pressure [psig]	667 psig
Molecular sieve [%]	100 %
Net volume [foz US]	7.63 Fluid Ounce US
Net volume [l]	0.226 L
Oil free refrigerants	R1234ze(E) R134a R513A R515A
Outlet 1 connection size [in]	5/8 in
Outlet connection type	Solder, ODF
Packing format	Multi pack
PED category	Art. 4, par. 3
Product description	Liquid line filter drier
Quantity per packing format	12 pc
REACH Candidate List substances	No
Refrigerants	R1233zd(E), R1234yf, R1234ze(E), R125, R134a, R22/R407C, R23, R290, R32, R404A, R407A, R407F, R407H, R410A, R422B, R422D, R438A, R444B, R448A, R449A, R449B, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R463A, R507A, R513A, R515B, R516A, R600
Serviceable	No
Shell volume [foz US]	11.97 Fluid Ounce US
Shell volume [l]	0.35 L
Solid core surface [cm2]	183 cm ²
Solid core surface [in2]	28.34 in ²
Solid core volume [cm3]	128 cm ³
Solid core volume [in3]	7.84 in ³
Temperature range [°C] [max]	70 °C
Temperature range [°C] [min]	-40 °C
Temperature range [°F] [max]	160 °F

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Temperature range [°F] [min]	-40 °F
Type designation	DML 165S
UL approval file name	SA6398
UL approved refrigerants	R125, R134a, R22, R23, R404A, R407A, R407C, R407F, R410A, R422B, R422D, R438A, R448A, R449A, R449B, R450A, R452A, R507A, R513A
UL mark	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.